

MATERIAL SAFETY DATA SHEET

This MSDS complies with OSHA's Hazard Communication Standard CFR 1910.1200 and OSHA Form 174.

N/A SIGNIFIES NON-APPLICABLE

IDENTITY AND SUPPLIERS INFORMATION

PRODUCT NAME:	NEW LIFE II	CHEMICAL FAMILY:		<table><tr><th>HMIS HAZARDOUS MATERIALS IDENTIFICATION SYSTEM</th><th>RATING</th></tr><tr><td>HEALTH</td><td>0</td></tr><tr><td>FLAMMABILITY</td><td>0</td></tr><tr><td>REACTIVITY</td><td>1</td></tr><tr><td>MAX PERSONAL PROTECTION</td><td>B</td></tr></table>	HMIS HAZARDOUS MATERIALS IDENTIFICATION SYSTEM	RATING	HEALTH	0	FLAMMABILITY	0	REACTIVITY	1	MAX PERSONAL PROTECTION	B
HMIS HAZARDOUS MATERIALS IDENTIFICATION SYSTEM	RATING													
HEALTH	0													
FLAMMABILITY	0													
REACTIVITY	1													
MAX PERSONAL PROTECTION	B													
PRODUCT NUMBER	A145	FORMULA:	PROPRIETARY											
SUPPLIER'S NAME:	GENERAL PRODUCTS & SUPPLY, INC.	PHONE NUMBER:	(724) 327-7200											
SUPPLIER'S ADDRESS:	101 TECHNOLOGY LANE	EMERGENCY NO.:	800-255-3924											
	EXPORT, PA 15632	DATE PREPARED:	07/26/05											
PROPER SHIPPING NAME: CONSUMER COMMODITY (ORM-D)														

SECTION 1 - INGREDIENT IDENTIFICATION AND INFORMATION

CHEMICAL NAME	CARC.	CAS NO.	WT %	SKIN	PEL	TWA-TLV	313/CHEM
Food Grade Mineral Oil	NO	8042-47-5	10-20	NO	N/E	N/E	NO
Citrus Terpene	NO	5989-27-5	01-10	NO	400ppm	400ppm	NO
Liquified Petroleum Gas	NO	68476-85-7	10-20	NO	1000ppm	1000ppm	NO

SECTION 2 - PHYSICAL/CHEMICAL PROPERTIES

SECTION 3 - FIRE/EXPLOSION HAZARD DATA

BOILING POINT: ~158°F
VAPOR PRESSURE: (mm Hg @68°F) 60
VAPOR DENSITY: >1
SOLUBILITY IN WATER: Complete
SPECIFIC GRAVITY: 0.960
pH RANGE: 11.0
VOC CONTENT (% by weight) ~17.7%
EVAPORATION RATE: (Ether=1) N/D
PHYSICAL DESCRIPTION: White Jel Liquid with Citrus Scent

FLAMMABILITY: (FLAME PROJECTION) Flammable Spray
AUTO IGNITION TEMP: N/A
FLASH POINT: None to Boiling (TOC)
FLAMMABILITY LIMITS: %UEL N/D %LEL N/D
EXTINGUISHER MEDIA: Foam, CO2, dry media
SPECIAL FIRE FIGHTING PROCEDURES: Wear self-contained breathing apparatus and protective clothing. Cool fire exposed containers to prevent rupturing.
UNUSUAL FIRE/EXP. HAZARDS: Exposure to temperatures above 120° may cause bursting.

SECTION 4 - REACTIVITY HAZARD DATA

STABILITY: Stable
HAZARDOUS POLYMERIZATION: Will not occur
INCOMPATIBILITY: Avoid contact with strong oxidizing agents.
CONDITIONS TO AVOID: None
HAZARDOUS DECOMPOSITION PRODUCTS: Carbon Dioxide and Carbon Monoxide.

SECTION 5 - HEALTH HAZARD DATA AND FIRST AID

PRIMARY ROUTES OF ENTRY:
EFFECTS OF OVEREXPOSURE:

EMERGENCY & FIRST AID PROCEDURES:

SKIN:	Frequent or prolonged skin contact may cause irritation. May aggravate existing skin conditions.	SKIN:	Wash with soap and water. If irritation persists seek medical attention immediately.
EYES:	May cause slight irritation.	EYES:	Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists get medical attention immediately.
INHALATION:	Inhalation of mist can cause irritation of nasal and respiratory passages. Abusive or excessive inhalation may cause irritation to the upper respiratory tract, dizziness, nausea and other central nervous system effects.	INHALATION:	Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration.
INGESTION:	Can cause gastrointestinal irritation, nausea, vomiting and diarrhea. Aspiration of material into the lungs can cause chemical pneumonitis and delayed pulmonary edema. Minimal toxicity.	INGESTION:	Do not induce vomiting. Seek medical attention immediately.

SECTION 6 - CONTROL AND PROTECTIVE MEASURES

RESPIRATORY PROTECTION: None needed for proper use in accordance with label directions.
PROTECTIVE GLOVES: Chemical resistant if hand contact will be made.
EYE PROTECTION: Always wear safety glasses or chemical proof goggles when working with chemicals.
VENTILATION REQUIREMENTS: Provide local exhaust to keep air concentrations of ingredients listed in Section II below established exposure limits.
HYGENIC WORK PRACTICES: Do not eat, drink or smoke in work area. Wash hands after handling. Launder contaminated clothing.

SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IF MATERIAL IS SPILLED OR RELEASED: Allow propellant to evaporate. Maintain local exhaust and adequate ventilation. No smoking. Keep sparks, heat sources and open flame far away from spill or leak. Cover with absorbent material and sweep up. Wash area to prevent slipping. Dispose of soaked absorbent material in accordance with Federal, State and local laws.

WASTE DISPOSAL METHODS: Aerosol cans, when emptied and depressurized through normal use, pose no disposal hazard and should be recycled. Consult Federal, State and local authorities for approved procedures.

PRECAUTIONS IN HANDLING AND STORAGE: For Industrial and Institutional use only. Store in a cool, dry area away from heat or open flame. Do not store at temperatures above 120°F.

OTHER PRECAUTIONS: Read and follow label directions. Keep out of reach of children.

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without any warranty or guarantee of any kind.