

This MSDS complies with OSHA's Hazard Communication Standard CFR 1910.1200 and OSHA Form 174.

N/A SIGNIFIES NON-APPLICABLE

IDENTITY AND SUPPLIERS INFORMATION

PRODUCT NAME:	NO SWEAT	CHEMICAL FAMILY:		<table><tr><th>HMIS HAZARDOUS MATERIALS IDENTIFICATION SYSTEM</th><th>RATING</th></tr><tr><td>HEALTH</td><td>2</td></tr><tr><td>FLAMMABILITY</td><td>2</td></tr><tr><td>REACTIVITY</td><td>1</td></tr><tr><td>MAX PERSONAL PROTECTION</td><td>B</td></tr></table>	HMIS HAZARDOUS MATERIALS IDENTIFICATION SYSTEM	RATING	HEALTH	2	FLAMMABILITY	2	REACTIVITY	1	MAX PERSONAL PROTECTION	B
HMIS HAZARDOUS MATERIALS IDENTIFICATION SYSTEM	RATING													
HEALTH	2													
FLAMMABILITY	2													
REACTIVITY	1													
MAX PERSONAL PROTECTION	B													
GMP PRODUCT NUMBER:	A302	FORMULA:	PROPRIETARY											
SUPPLIER'S NAME:	GENERAL PRODUCTS & SUPPLY, INC.	PHONE NUMBER:	(724) 327-7200											
SUPPLIER'S ADDRESS:	101 TECHNOLOGY LANE	EMERGENCY NO.:												
	EXPORT, PA 15632													
PROPER SHIPPING NAME:														

SECTION 1 - INGREDIENT IDENTIFICATION AND INFORMATION

CHEMICAL NAME	CARC.	CAS NO.	WT %	CHEM III	PEL	TWA/TLV	SKIN
Trichloroethylene	No	79-01-6	20-40		50 ppm	50 ppm	No
Parachlorobenzotrifluoride	No	98-56-6	10-20		N/E	N/E	No
Stearic Acid	No	57-11-4	01-10		N/E	N/E	No
Titanium Dioxide	No	13463-67-7	01-10		N/E	N/E	No
Liquified Petroleum Gas	No	68476-85-7	20-40		1000 ppm	1000 ppm	No

SECTION 2 - PHYSICAL/CHEMICAL PROPERTIES

SECTION 3 - FIRE/EXPLOSION HAZARD DATA

BOILING POINT: ~160°F
VAPOR PRESSURE: (psig @ 72°F) 50
VAPOR DENSITY (air = 1): >1
SOLUBILITY IN WATER: Slight
SPECIFIC GRAVITY @ 75°F (water = 1): 1.358
pH RANGE: N/A
TOTAL VOC%: ~74.5%
PHYSICAL DESCRIPTION: Viscous white liquid/solvent

FLAMMABILITY: Extremely Flammable Spray
AUTO IGNITION TEMP: N/E
FLASH POINT (Concentrate Only): ~114°F (T.O.C.)
FLAMMABILITY LIMITS: N/E %UEL %LEL
EXTINGUISHER MEDIA: Foam, CO2, Dry Media
SPECIAL FIRE FIGHTING PROCEDURES: Wear self-contained breathing apparatus and protective clothing. Cool fire exposed containers to prevent rupturing
UNUSUAL FIRE/EXP. HAZARDS: Exposure to temperatures above 120°F may cause bursting.

SECTION 4 - REACTIVITY HAZARD DATA

STABILITY: Stable
HAZARDOUS POLYMERIZATION: Will not occur
INCOMPATIBILITY: Strong oxidizing agents
CONDITIONS TO AVOID: N/A
HAZARDOUS DECOMPOSITION PRODUCTS: Carbon Dioxide, Carbon Monoxide decomposition of Chlorinated compounds may result in chlorine containing gases including, but not limited to, phosgene.

SECTION 5 - HEALTH HAZARD DATA AND FIRST AID

ACUTE EFFECTS:	FIRST AID PROCEDURES:
SKIN: Frequent or prolonged contact may cause irritation.	SKIN: Wash affected area with soap and water. If irritation persists seek medical attention.
EYES: May cause mild irritation including redness, burning and tearing.	EYES: Flush with large amounts of cool running water for at least 15 minutes, while holding upper and lower lids open. If irritation persists, get medical attention immediately.
INHALATION: Inhalation of mist can cause irritation of nasal and respiratory passages. Abusive or excessive inhalation may cause irritation to the upper respiratory tract, dizziness, nausea, and other central nervous system effects.	INHALATION: Remove to fresh air. Seek medical attention immediately. If breathing stops, give artificial respiration.
INGESTION: Can cause gastrointestinal irritation, nausea, vomiting, and diarrhea. Aspiration of material into the lungs can cause chemical pneumonitis.	INGESTION: DO NOT INDUCE VOMITING. Seek medical attention immediately.

SECTION 6 - CONTROL AND PROTECTIVE MEASURES

RESPIRATORY PROTECTION: None needed for proper use in accordance with label directions.
PROTECTIVE GLOVES: None needed for proper use in accordance with label directions.
EYE PROTECTION: None needed unless it is anticipated that a splash or spray back will occur, then wear safety glasses or chemical proof goggles.
VENTILATION REQUIREMENTS: Provide local exhaust to keep TLV of Section I ingredients below acceptable limits.
OTHER PROTECTIVE CLOTHING: None known.

SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IF MATERIAL IS SPILLED OR RELEASED: Allow propellant to evaporate. Maintain local exhaust and adequate ventilation. No smoking. Keep sparks, heat sources, and open flames far away from spill or leak. Cover with absorbent material and sweep up. Wash area to prevent slipping. Dispose of soaked absorbent material in accordance with Federal, State, and local laws.

WASTE DISPOSAL METHODS: Aerosol cans, when emptied and depressurized through normal use, pose no disposal hazard and should be recycled. Consult Federal, State, and local authorities for approved procedures.

PRECAUTIONS IN STORAGE AND HANDLING: N/A

OTHER PRECAUTIONS: N/A

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without any warranty or guarantee of any kind.