

MATERIAL SAFETY DATA SHEET

This MSDS complies with OSHA's Hazard Communication Standard CFR 1910.1200 and OSHA Form 174.

N/A SIGNIFIES NON-APPLICABLE

IDENTITY AND SUPPLIERS INFORMATION

PRODUCT NAME: C.T.R. WHITE
GMP PRODUCT NUMBER: A303
SUPPLIER'S NAME: GENERAL PRODUCTS & SUPPLY, INC.
SUPPLIER'S ADDRESS: 101 TECHNOLOGY LANE
EXPORT, PA 15632
PROPER SHIPPING NAME: CONSUMER COMMODITY (ORM-D)

CHEMICAL FAMILY:
FORMULA: PROPRIETARY
PHONE NUMBER: (724) 327-7200
EMERGENCY NO.: 800-255-3924
DATE PREPARED: 07/22/04

HMIS HAZARDOUS MATERIALS IDENTIFICATION SYSTEM	RATING
HEALTH	1
FLAMMABILITY	3
REACTIVITY	1
MAX PERSONAL PROTECTION	I

SECTION 1 - INGREDIENT IDENTIFICATION AND INFORMATION

CHEMICAL NAME	CARC.	CAS NO.	WT %	SARA III	PEL	TWA-TLV	STEL-TLV
ETHYL ALCOHOL	NO	64-17-5	20-30		400 ppm	400 ppm	
ACETONE	NO	67-64-1	10-20		1000 ppm	1000 ppm	
TITANIUM DIOXIDE	NO	13463-67-7	01-10		15mg/m ³	10mg/m ³	
TOLUENE	YES	108-88-3	01-10		100 ppm	50 ppm	
LIQUIFIED PETROLEUM GAS	NO	68476-85-7	30-40		1000 ppm	1000 ppm	
HYDROUS MAGNESIUM SILICATE	NO	14807-96-6	10-20		20 mppcf	2 mg/m ³ (dust)	

SECTION 2 - PHYSICAL/CHEMICAL PROPERTIES

SECTION 3 - FIRE/EXPLOSION HAZARD DATA

BOILING POINT: 152°F
VAPOR PRESSURE: (mm Hg) 60
VAPOR DENSITY: (Air=1) >1
SOLUBILITY IN WATER: Soluble
SPECIFIC GRAVITY: (H₂O=1) @ 75°F: 1.08
pH RANGE: N/A
EVAPORATION RATE: (Ether=1) N/A
PHYSICAL DESCRIPTION: White liquid, mint odor

FLAMMABILITY: Extremely Flammable Spray
FLASH POINT: 34°F
FLAMMABILITY LIMITS: N/A
EXTINGUISHER MEDIA: Foam, CO₂, Dry Media
SPECIAL FIRE FIGHTING PROCEDURES: Wear self-contained breathing apparatus and protective clothing. Cool fire exposed containers to prevent rupturing.
UNUSUAL FIRE/EXP. HAZARDS: Exposures to temperatures above 120°F may cause bursting.

SECTION 4 - REACTIVITY HAZARD DATA

STABILITY: Stable
HAZARDOUS POLYMERIZATION: Will not occur
INCOMPATIBILITY: Avoid contact with strong oxidizing agents.
CONDITIONS TO AVOID: N/A
HAZARDOUS DECOMPOSITION PRODUCTS: Carbon Monoxide and Carbon Dioxide

SECTION 5 - HEALTH HAZARD DATA AND FIRST AID

ACUTE EFFECTS:	FIRST AID PROCEDURES:
SKIN: Frequent or prolonged contact may cause irritation. May aggravate existing skin conditions.	SKIN: Wash with soap and water. If irritation persists seek medical attention.
EYES: May cause moderate irritation. Repeat exposure may cause conjunctive inflammation.	EYES: Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists get medical attention immediately.
INHALATION: Inhalation of mist can cause irritation of nasal and respiratory passages. Abusive or excessive inhalation may cause irritation to the upper respiratory tract, dizziness, shortness of breath, chronic cough, nausea, damage to the lungs and other central nervous system effects. May aggravate existing disorders.	INHALATION: Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration.
INGESTION: Can cause gastrointestinal irritation, nausea, vomiting and diarrhea. Aspiration of material into the lungs can cause chemical pneumonitis.	INGESTION: Do not induce vomiting. Seek medical attention immediately.

SECTION 6 - CONTROL AND PROTECTIVE MEASURES

RESPIRATORY PROTECTION: If work place exposure limit of product or any component is exceeded, a NIOSH/MSHA approved air purifying respirator is advised in absence of proper environmental control.

PROTECTIVE GLOVES: Use chemical resistant gloves.

EYE PROTECTION: Wear safety glasses or chemical-proof goggles.

VENTILATION REQUIREMENTS: Provide local exhaust to keep air concentrations of ingredients listed in Section II below established exposure limits.

OTHER PROTECTIVE CLOTHING: N/A

SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IF MATERIAL IS SPILLED OR RELEASED: Allow propellant to evaporate. Maintain local exhaust and adequate ventilation. No smoking. Keep sparks, heat sources and open flame far away from spill or leak. Cover with absorbent material and sweep up. Wash area to prevent slipping. Dispose of soaked absorbent material in accordance with Federal, State and local laws.

WASTE DISPOSAL METHODS: Aerosol cans, when emptied and depressurized through normal use, pose no disposal hazard and should be recycled. Consult Federal, State and local authorities for approved procedures.

PRECAUTIONS IN HANDLING AND STORAGE: For Industrial and Institutional use only. Store in a cool, dry area away from heat or open flame. Do not store at temperatures above 120°F.

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without any warranty or guarantee of any kind.