

ZINK-KOTE protects iron, steel or aluminum for corrosion when exposed to weather or otherwise corrosive conditions. Uses are on air conditioning and heat systems, farm equipment, culverts, highway signs, marine equipment and boats, oilrigs and offshore drilling structures and most other metal objects that are subject to corrosion. If required, this product may be painted over.

ZINK-KOTE meets or exceeds military specifications Mil-P-46105 weld thru primer, US Navy; galvanizing repair specification Mil-P-21035; Mil-T-26433 for towers (Temperate and Arctic Zones).

DIRECTIONS

For maximum results, **ZINK-KOTE** should be applied to clean, dry metal. However, very efficient results are obtained over firmly adherent rust after wire brushing and removal of all oil and grease. Old paint should be removed. Mill scale and deep rust must be sand blasted.

Shake the can until agitator moves freely. Spray from 10 to 12 inches, in a sweeping motion, across the work area.

IMPORTANT: When finished spraying, turn can upside down and spray for 2 seconds. This will keep the valve from plugging.

CAS Numbers: Contains xylene (1330-20-7), methylene chloride (75-09-2), propane (74-98-6), and zinc dust and resin binder (7440-66-6).



CAUTION

Use with adequate ventilation. Avoid inhalation of spray mist or vapors. Avoid contact with eyes and skin. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F.

FIRST AID

IF IN EYES: Flush with water for 15 minutes. If irritated, see a physician.

IF ON SKIN: Wash with soap and water. If irritated, see a physician.

IF INHALED: Remove to fresh air. Resuscitate if necessary. Get medical aid.

IF SWALLOWED: Do not induce vomiting. Call a physician.

KEEP OUT OF REACH OF CHILDREN



Reorder A306
800-548-2080

HMIS RATING
2 - FLAMMABILITY
2 - HEALTH
0 - REACTIVITY
B - PERSONAL PROPERTY

SOLD EXCLUSIVELY BY:


General Products & Supply Inc.

Murrysville Business Park
Export, PA 15632


GMP
Chemical Solutions

101 Technology Lane
(800) 548-2080