

No Chlorinated Solvents
(No 1,1,1-Trichloroethane)

RUSTECH II IN-A-CAN chemically neutralizes rust and leaves a tough, long-term, rust preventative coating.

RUSTECH II IN-A-CAN seals, protects and prolongs the life of ferrous metal. Rusted areas turn into a black protective finish. The protective barrier, upon curing, should be painted with a high quality oil-based paint for added protection.

DIRECTIONS

For best results, do not apply if the surface temperature is below 50°F or above 90°F. Surfaces must be clean, dry and free of grease, dirt and oil. Prepare surface by brushing the loose rust from the surface using a wire brush or sand paper. Clean the surface to remove grease and grime.

Shake well before use.

Hold can 8-12 inches from surface and spray a thin coat onto the surface. After the surface has dried, it will turn black. Then apply a second thin coat. Allow 48 hours to completely cure before painting while protecting it from rain or dew.

For long lasting protection, seal with two coats of a high quality oil-based paint.

Store in a cool dry place, protected from freezing or temperature above 100°F.

DANGER: **EXTREMELY FLAMMABLE**

May cause burns and/or severe irritation to the eyes, skin, stomach and respiratory tract. Prolonged or repeated contact may dry or defat the skin and lead to inflammation (i.e. dermatitis). Possible aspiration hazard – may cause inflammation of the lungs. May cause nausea, vomiting, pain, and stomach upset (e.g. diarrhea). May affect the following organs upon prolonged or repeated overexposure: Liver, Kidneys. Nervous system. Heart and/or circulatory system. Keep away from heat, sparks, and flames. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F (49°C) as container may burst. Avoid prolonged exposure to sunlight. Use with adequate ventilation.

GMP
Chemical Solutions

A307

GENERAL MAINTENANCE PRODUCTS

RUSTECH II IN-A-CAN

- Chemically Stops & Converts Rusted Metal to a Non-Rusted Surface
- Forms a Tough, Resistant, Stable Black Coating
- No Major Surface Preparation
- Can Be Painted After Curing
- Prevents Future Rusting on Surfaces Exposed to Rain, Sun & Salt
- Non-Flammable When Dry

DANGER:
EXTREMELY FLAMMABLE.
MAY CAUSE BURNS TO EYES,
SKIN AND RESPIRATORY TRACT.
CONTENTS UNDER PRESSURE.
KEEP OUT OF REACH OF CHILDREN
Read Side Panel For Additional Precautions.

Net Weight: 13 oz. (369g)

F
O
R

P
R
O
F
E
S
S
I
O
N
A
L

O
R

I
N
D
U
S
T
R
I
A
L

U
S
E

O
N
L
Y

FIRST AID

IF IN EYES: Flush eyes and under eyelids with water for at least 15 minutes. Obtain medical attention.

IF ON SKIN: Flush skin with plenty of water for 15 minutes. Remove contaminated clothing, and launder before reuse. If irritation is persistent, contact a physician.

IF SWALLOWED: Contact physician or poison control center immediately. Rinse mouth with water and give affected person 1-2 glasses of water to dilute. Do not induce vomiting unless instructed by a physician or poison control center. Never give anything by mouth to an unconscious person.

IF INHALED: Remove person to fresh air. If symptoms develop, seek medical attention. If not breathing, give artificial respiration.

See M.S.D.S. for complete safety information.

KEEP OUT OF REACH OF CHILDREN

24 HOUR MEDICAL EMERGENCY: 1-800-228-5635

CONTAINS NO OZONE DEPLETING CHEMICALS!

8346 • 090804



Reorder A307
800-548-2080

SOLD EXCLUSIVELY BY:


General Products & Supply Inc.

Murrysville Business Park
Export, PA 15632

HMIS RATING	
2 - HEALTH	
4 - FLAMMABILITY	
1 - REACTIVITY	
A - PROTECTIVE EQUIPMENT	

GMP
Chemical Solutions

101 Technology Lane
(800) 548-2080