

GEAR & CHAIN LUBRICANT has a tacky adhesiveness that continuously recoats and lubricates all gear surfaces. It is extremely effective when used under water. **GEAR & CHAIN LUBRICANT** forms a film that resists rust and corrosion, increases life of all gears, and the extreme pressure capacity minimizes squeeze out

DIRECTIONS

Shake well before using. Spray a liberal amount in short bursts from 12 to 15 inches. Repeat as needed.

CAS Numbers: Contains methylene chloride (75-09-2), petroleum distillate (8052-41-3), and isobutene/propane blend (75-28-5 and 74-98-6).

CAUTION

Do not spray near heat, sparks, or open flame. Use with adequate ventilation. Avoid breathing spray mist and vapor. Deliberately concentrating and inhaling the vapor of the contents may be harmful or fatal. Do not puncture or incinerate the container. Do not store at temperatures above 120°F.



GENERAL MAINTENANCE PRODUCTS



(CAUTION , cont.) Do not place near source of heat, radiator, or in direct sunlight. High temperatures may cause the container to burst. Read the Material Safety Data Sheet before use.

FIRST AID

IF IN EYES: Flush with water for 15 minutes. If irritated, see a physician.

IF ON SKIN: Wash with soap and water. If irritated, see a physician.

IF INHALED: Remove to fresh air. Resuscitate if necessary. Seek medical attention.

IF SWALLOWED: Do not induce vomiting. Call a physician immediately.

KEEP OUT OF REACH OF CHILDREN



Reorder A380
800-548-2080

HMIS RATING
2 - FLAMMABILITY
2 - HEALTH
0 - REACTIVITY
B - PERSONAL PROPERTY

SOLD EXCLUSIVELY BY:


General Products & Supply Inc.


GMP
Chemical Solutions

Murrysville Business Park
Export, PA 15632

101 Technology Lane
(724) 627-7200