

**C.W.R.C.** provides a thick foam that clings to vertical surfaces. As foam breaks, lubricant penetrates into wire rope and roller chain mechanisms. Deposits a Molybdenum Disulfide based grease and provides surfaces with superior lubricating properties. Protects against high temperature and extreme pressure environments. Grease will not break down, fly off, or wash away with water or steam. Retains lubricating properties under heavy shock load, acidic environments and salt spray. Prevents surface oxidation and corrosion. Super high tack formula provides active lubricant dispersion while equipment is in operation.

## CAN BE USED ON

Chains, Wire Cable, Open Gears, Sprockets, Chain Saws, Drag Lines, Power Drives, Fittings, Booms, Road and Construction Machinery, Hoists, Winches, Cranes, Material Handling Equipment, Tow Lines, Linkages, and Roller Assemblies.

## USED BY

- Shipyards • Mining • Railroads • Factories
- Construction Steel Mills • Road Equipment
- Material Handling Companies
- Containerized Shipping Companies

## DIRECTIONS: SHAKE WELL

Read all instructions before using **C.W.R.C.**

1. Shake vigorously until agitator ball inside can rattles freely for one minute. Shake can occasionally throughout application.
2. Spray area to be treated from a distance of 8 to 10 inches.
3. Allow foam to penetrate and set-up to occur.
4. For best results, repeat application periodically.

**CAS Numbers:** Mineral Oil, Petroleum Distillates, Solvent-Dewaxed Heavy Paraffinic (CAS#64742-65-0), Propane (CAS#74-98-6), Butane (CAS#106-97-8), Isobutane (CAS# 75-28-5), Molybdenum (IV) Sulfide (CAS# 1317-33-5).

## PRECAUTIONARY STATEMENT:

If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

SOLD EXCLUSIVELY BY:

  
General Products & Supply Inc.  
101 Technology Lane  
Export, PA 15632



800-548-2080  
www.gmpgeneralproducts.com

VOC Content: 19.5%

Reorder A381  
800-548-2080



# GMP

Chemical Solutions

A381

## GENERAL MAINTENANCE PRODUCTS

# C.W.R.C. With Moly

## Chain, Wire, Rope and Cable Lube

- Lubricates
- Penetrates
- Clinging Foam
- Rust Inhibitors
- Now with MOLYBDENUM

**DANGER:**  
**EXTREMELY FLAMMABLE**  
**AEROSOL, PRESSURIZED**  
**CONTAINER MAY BURST**  
**IF HEATED.**

Net Wt. 16 oz. (453 grams)

#497255

12065

10/15

4CP

#497255GENPR-P20