

**SHAKE WELL BEFORE USING
FEATURES:**

- Temperature range of -110°F to 1000°F.
- Very low coefficient of friction.
- Chemically inert to water, oil, alkalies and many acids.
- Will not attract dust.
- Burnishes into metal for excellent anti-seize and anti-friction properties.

DIRECTIONS:

1. Clean and dry surfaces to be sprayed.
2. Hold can 8 to 10 inches from surface.
3. Spray thin even coat.

**Read Material Data Safety Sheet before using.
KEEP OUT OF REACH OF CHILDREN.**

4-238-4



- IMPORTANT -

Invert can and clear valve after use.

DANGER! Do not spray near heat, sparks, or open flame. Contains Perchloroethylene (CA#127-18-4), Isopropanol (CAS#67-63-0), Toluene (CAS#108-88-3), Acetone (CAS#67-64-1), Molybdenum Disulfide (CAS#1317-33-5), Propane (CAS#74-98-6), Isobutane (CAS#75-28-5), n-Butane (CAS#106-97-8). If swallowed, do not induce vomiting. **CALL A PHYSICIAN IMMEDIATELY.** Use with adequate ventilation. Avoid breathing spray mist and vapor. Deliberately concentrating and inhaling of the vapor of the contents may be harmful or fatal. Avoid frequent or prolonged contact with skin and eyes. For skin contact, wash with soap and water. Provide oxygen or fresh air if overcome by vapor. Do not puncture or incinerate (burn) container. Do not store at temperatures above 120°F. Do not place near source of heat, radiator or in direct sunlight. High temperatures may cause the container to burst. If sprayed in eyes, flush thoroughly with water for 15 minutes. Get medical help.



Reorder A387
800-548-2080

HMIS RATING	
4 - FLAMMABILITY	
2 - HEALTH	
0 - REACTIVITY	
B - PERSONAL PROPERTY	

SOLD EXCLUSIVELY BY:


General Products & Supply Inc.

GMP
Chemical Solutions

Murrysville Business Park
Export, PA 15632

101 Technology Lane
(800) 548-2080