CONFORMS TO TESTS SPECIFIED IN ASTM STP 332

PENELUBE NG* contains no silicones or chlorinated solvents which affect plastics, lacquers, insulation, and paint. Contains Molybdenum disulfide and tetrafluoroethylene particles for added pressure and wear resistance.

Forceful jet-spray aids in rapid penetration through rust and corrosion to free frozen parts. Leaves a long lasting lubricating film which defends against future corrosion. Provides effective lubrication over a broad range of temperatures and pressures.

® - TEFLON is a registered trademark of E.I. Dupont deNemours & Co., Inc.

DIRECTIONS: Saturate part to be loosened and allow product to penetrate for a moment before attempting to break free. For heavily encrusted pieces a wire brush may be used to help remove corrosion. Apply a light final spray to all parts prior to reassembly.

NOTE - SPECIAL VALVE ALLOWS CAN TO BE SPRAYED WHILE HELD IN ANY POSITION.



DANGER: Contains Aliphatic Mineral Spirits (64741-65-7), Mineral Oil (8042-47-5), Acetone (67-64-1), Polytetrafluoroethylene (9002-84-0) and Carbon Dioxide Propellant (124-38-9). Use only in a well ventilated area. Do not use near heat, sparks or open flame. Avoid contact with eyes and prolonged contact with skin. Do not permit product to contaminate tobacco products. Wash hands before smoking. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F.

F

0

0

F

Е

S

S

T

 \cap

Ν

Α

R

N

D

U

S

Т

R

I

Α

L

U

S E

0

Ν

L

Y

FIRST AID:

EXCESSIVE INHALATION: Remove to fresh air and call a physician.

IF SWALLOWED: Do not induce vomiting. Get medical attention.

IF EYE CONTACT: Flush with water for 15 minutes, lifting upper and lower lids. Get medical attention.

IF SKIN CONTACT: Wash affected area immediately with

soap and water. If irritation persists, get medical attention.

KEEP OUT OF REACH OF CHILDREN

