

SHAKE WELL BEFORE USING FEATURES

- Three Products in One:
 1. High temp anti-seize for nuts, bolts, studs, etc.
 2. Premium quality lubricant for bearings, slides, etc.
 3. Protective coating for service in highly corrosive elements
- Prevents galling, seizing, and galvanizing action

DIRECTIONS

SPRAY PRODUCT ONLY AT TEMPERATURES ABOVE 60°F.

1. Shake can vigorously for one minute after mixing ball begins to rattle.
2. Make sure surface is cleaned of all dirt, grease and grime.
3. Spray liberal amount from distance of 8-10 inches.
4. Invert can after use and spray short bursts to clear valve.

CAS Numbers: Methylene Chloride (75-09-2), Copper (7440-50-8), Butane (106-97-8), Propane (74-98-6), Isobutane (75-28-5).

PRECAUTIONARY STATEMENT

If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Do not handle until all safety precautions have been read and understood. Collect spillage. In case of fire: Use water fog, dry chemical or carbon dioxide to extinguish. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell. IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF exposed or concerned: Get medical advice/attention. Keep cool. Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Dispose of contents and container in accordance with all local, regional, national and international regulations. **WARNING:** This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

Read Safety Data Sheet before using.

**KEEP OUT OF REACH OF CHILDREN. FOR INDUSTRIAL USE ONLY.
NOT FOR SALE IN THE STATES OF CALIFORNIA AND NEW JERSEY.**

SOLD EXCLUSIVELY BY:


General Products & Supply Inc.

101 Technology Lane
Export, PA 15632



BUY USA

800-548-2080

www.gmpgeneralproducts.com

Reorder A392
800-548-2080




GMP
Chemical Solutions

A392

GENERAL MAINTENANCE PRODUCTS

GALL STOP

Anti Seize Lubricant

- 60° to 2000°F 
- High E.P. Capability
- Excellent Adhesion
- Lubricates, Seals, Protects
- Non Gumming, Non Melting
- Compatible with Other Lubricants

DANGER:

Extremely flammable aerosol. Pressurized container may burst if heated. May cause respiratory irritation. Harmful if swallowed. May be harmful in contact with skin. May cause damage to organs through prolonged or repeated exposure. Causes skin irritation. Causes serious eye irritation. Suspected of causing cancer. Very toxic to aquatic life with long lasting effects.

Net Wt. 14 oz. (396 grams)