

**WELDING ANTI-SPATTER** eliminates welding spatter marks from your work. No more grinding or chiseling to remove stubborn spatter. Simply spray work lightly before welding – then wipe spatter off with a dry rag!

#### DIRECTIONS

1. Shake contents thoroughly. 2. Use firm finger pressure on sprayhead, making sure arrow on sprayhead is pointed away from you. 3. Hold can 4-12" from work. Apply light coat evenly to entire surface area you wish to protect. 4. **DO NOT INVERT CANS AND SPRAY.** IF CLOGGING OCCURS, remove actuator and soak in mild solvent. Operates best at room temperature (APPROX. 70°). CAS Numbers: Contains Methylene Chloride (75-09-2), Carbon Dioxide (124-38-9), and Silicone Fluid (68037-76-3).

#### CAUTION

**HARMFUL OR FATAL IF SWALLOWED. CONTENTS UNDER PRESSURE.** Vapors may ignite explosively. Keep away from heat, sparks, and flame. Do not smoke. Extinguish all flames, electric motors and other sources of ignition during use and until all vapors are gone. Do not puncture or incinerate (burn) container. Exposure to heat or prolonged exposure to sun may cause bursting. Do not expose to heat or store at temperatures above 120°F. This product contains a chemical known to the State of California to cause cancer in certain laboratory animals. Please read the proper disposal information so as to prevent possible ground water contamination. Refer to MSDS for additional information.

**VAPORS HARMFUL:** Overexposure may affect the brain or nervous system causing dizziness, headache, or nausea. May cause eye, skin, nose, and throat irritation. Use only with adequate ventilation. Do not breathe dust, vapors, or spray mist. To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air or wear respiratory protection (NIOSH/MSHA TC23C or approved equivalent) or leave the area.

**GMP**  
Chemical Solutions

A394

### GENERAL MAINTENANCE PRODUCTS

## WELDING ANTI-SPATTER

- Prevents Spatter
- Time Saver
- Easy Application
- Easy Clean Up

**CAUTION:** Harmful or Fatal If Swallowed. Vapors Harmful. Contents Under Pressure.

**KEEP OUT OF REACH OF CHILDREN**  
**NET CONTENTS: 12.6 OZ(S)**

#### CAUTION

**TARGET ORGANS:** Kidneys, Liver, and Lungs.

**NOTICE:** Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

#### FIRST AID

**IF IN EYES:** Flush immediately with plenty of water for at least 15 minutes and get medical attention.

**IF ON SKIN:** Wash thoroughly with soap and water.

**IF INHALED:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately.

**IF SWALLOWED:** Do not induce vomiting. Call a physician immediately.

#### KEEP OUT OF REACH OF CHILDREN



Reorder A394  
800-548-2080

NFPA RATING
2 – HEALTH HAZARD
1 – FLAMMABILITY HAZARD
0 – REACTIVITY
- SPECIFIC HAZARD

SOLD EXCLUSIVELY BY:

  
General Products & Supply Inc.

**GMP**  
Chemical Solutions

Murrysville Business Park  
Export, PA 15632

101 Technology Lane  
(800) 548-2080