

METAL PARTS PROTECTOR is a long-term, flexible, non-tacky, dust resistant coating that will not crack, peel, flake, or chip over a wide temperature range (-40°F to +175°F). Adheres to most clean metal surfaces.

METAL PARTS PROTECTOR can be used on molds, offshore drilling parts, outdoor airport ground-handling equipment, castings, metal parts in ground or ocean transit, seasonal equipment in storage, and any metal part needing to be temporarily sealed against corrosion.

DIRECTIONS

SHAKE WELL BEFORE USING

Make sure surface is clean and dry. Spray a thin uniform film over parts. Allow approximately 5 minutes to set up.

For more severe storage conditions, a second coating can be applied within a few minutes. Complete setting of protective coating takes approximately 2 hours. Coating can be removed with mineral spirits or solvent degreaser.

CAS Numbers: Contains oxygenated hydrocarbon blend, liquefied petroleum gas (68476-85-7) and isoparaffinic hydrocarbon (64741-66-8).



CAUTION

Use only in a well ventilated area. Avoid contact with eyes or prolonged contact with skin. Do not puncture or incinerate container. Do not expose to heat, sparks, or open flame. Do not store at temperatures above 120°F.

FIRST AID

IF IN EYES: Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists, get medical attention immediately.

IF ON SKIN: Wash with soap and water. If irritation persists, seek medical attention.

IF INHALED: Remove to fresh air. Seek medical attention immediately. If breathing stops, give artificial respiration.

IF SWALLOWED: Do not induce vomiting. Seek medical attention.

KEEP OUT OF REACH OF CHILDREN



Reorder A396
800-548-2080

SOLD EXCLUSIVE BY:


General Products & Supply Inc.

Murrysville Business Park
Export, PA 15632

HMIS RATING	
3 - FLAMMABILITY	
1 - HEALTH	
0 - REACTIVITY	
B - PERSONAL PROPERTY	


GMP
Chemical Solutions

101 Technology Lane
(800) 548-2080