800-548-2080



www.gmpgeneralproducts.com

## SAFETY DATA SHEET (S.D.S.)

#### 1. Identification

Product number	A396
Product identifier	Metal Parts Protector
Company information	GENERAL PRODUCTS & SUPPLY 101 TECHNOLOGY LANE EXPORT, PA 15632 United States
Company phone	General Assistance 800-548-2080
Emergency telephone US	800-255-3924
Version #	01
Recommended use	COATING
Recommended restrictions	None known.

#### 2. Hazard(s) identification

Physical hazards	Flammable aerosols	
Health hazards	Specific target organ toxicity, repeated exposure	Category 1
	Aspiration hazard	Category 1
OSHA defined hazards	Not classified.	Category 1

#### Label elements



Danger
Extremely flammable aerosol. May be fatal if swallowed and enters airways. Causes damage to organs through prolonged or repeated exposure.
Keep away from heat/sparks/open flames/hot surfaces No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe gas. Wash thoroughly after handling. Do not eat, drink or smoke when using this product.
If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. Get medical advice/attention if you feel unwell.
Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Dispose of contents/container in accordance with local/regional/national/international regulations.
None known.
None.

## 3. Composition/information on ingredients

Mixtures			
Chemical name	Common name and synonyms	CAS number	%
Butane		106-97-8	20 - 40
Mineral Spirits		8052-41-3	20 - 40
Naphtha (petroleum), Light Alkylate		64741-66-8	10 - 20
Propane		74-98-6	10 - 20
Other components below reportable	elevels		20 - 40

*Designates that a specific chemica	al identity and/or percentage of composition has been withheld as a trade secret.
4. First-aid measures	
Inhalation	If symptoms develop move victim to fresh air. Get medical attention if symptoms persist.
Skin contact	Wash off with soap and water. Get medical attention if irritation develops and persists.
Eye contact	Rinse with water. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	Aspiration may cause pulmonary edema and pneumonitis. Dizziness. Prolonged exposure may cause chronic effects.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.
5. Fire-fighting measures	
Suitable extinguishing media	Foam. Powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. Use water spray to cool unopened containers. In the event of fire and/or explosion do not breathe fumes.
General fire hazards	Extremely flammable aerosol.
6. Accidental release meas	sures
Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe gas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.
7. Handling and storage	
Precautions for safe handling	Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Do not breathe gas. When using, do not eat, drink or smoke. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Level 3 Aerosol. Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS).

## 8. Exposure controls/personal protection

### **Occupational exposure limits**

Components	Туре	Value
Mineral Spirits (CAS 8052-41-3)	PEL	2900 mg/m3
		500 ppm
Propane (CAS 74-98-6)	PEL	1800 mg/m3
		1000 ppm
US. ACGIH Threshold Limi		
Components	Туре	Value
Butane (CAS 106-97-8)	STEL	1000 ppm
Mineral Spirits (CAS 8052-41-3)	TWA	100 ppm
US. NIOSH: Pocket Guide	to Chemical Hazards	
Components	Туре	Value
Butane (CAS 106-97-8)	TWA	1900 mg/m3
		800 ppm
Mineral Spirits (CAS 8052-41-3)	Ceiling	1800 mg/m3
	TWA	350 mg/m3
Propane (CAS 74-98-6)	TWA	1800 mg/m3
		1000 ppm
logical limit values	No biological exposure limits noted for	or the ingredient(s).
propriate engineering trols	should be matched to conditions. If a or other engineering controls to main	air changes per hour) should be used. Ventilation rates pplicable, use process enclosures, local exhaust ventilation tain airborne levels below recommended exposure limits. ished, maintain airborne levels to an acceptable level.
vidual protection measures	s, such as personal protective equipm	ent
Eye/face protection	If contact is likely, safety glasses with	n side shields are recommended.
Skin protection	Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.	
Skin protection Hand protection		gloves. Suitable gloves can be recommended by the glove
Hand protection	supplier. Use of an impervious apron is recom	
Hand protection Other	supplier. Use of an impervious apron is recom If permissible levels are exceeded us	mended. se NIOSH mechanical filter / organic vapor cartridge or an
Hand protection Other Respiratory protection	supplier. Use of an impervious apron is recom If permissible levels are exceeded us air-supplied respirator. Wear appropriate thermal protective When using do not smoke. Always of	mended. e NIOSH mechanical filter / organic vapor cartridge or an clothing, when necessary. bserve good personal hygiene measures, such as washing e eating, drinking, and/or smoking. Routinely wash work
Hand protection Other Respiratory protection Thermal hazards heral hygiene	supplier. Use of an impervious apron is recom If permissible levels are exceeded us air-supplied respirator. Wear appropriate thermal protective When using do not smoke. Always of after handling the material and before clothing and protective equipment to	mended. e NIOSH mechanical filter / organic vapor cartridge or an clothing, when necessary. bserve good personal hygiene measures, such as washing e eating, drinking, and/or smoking. Routinely wash work
Hand protection Other Respiratory protection Thermal hazards neral hygiene siderations Physical and chemical	supplier. Use of an impervious apron is recom If permissible levels are exceeded us air-supplied respirator. Wear appropriate thermal protective When using do not smoke. Always of after handling the material and before clothing and protective equipment to	mended. e NIOSH mechanical filter / organic vapor cartridge or an clothing, when necessary. bserve good personal hygiene measures, such as washing e eating, drinking, and/or smoking. Routinely wash work
Hand protection Other Respiratory protection Thermal hazards heral hygiene siderations Physical and chemical bearance	supplier. Use of an impervious apron is recom If permissible levels are exceeded us air-supplied respirator. Wear appropriate thermal protective When using do not smoke. Always of after handling the material and before clothing and protective equipment to <b>properties</b>	mended. e NIOSH mechanical filter / organic vapor cartridge or an clothing, when necessary. bserve good personal hygiene measures, such as washing e eating, drinking, and/or smoking. Routinely wash work
Hand protection Other Respiratory protection Thermal hazards neral hygiene siderations Physical and chemical	supplier. Use of an impervious apron is recom If permissible levels are exceeded us air-supplied respirator. Wear appropriate thermal protective When using do not smoke. Always of after handling the material and before clothing and protective equipment to	mended. e NIOSH mechanical filter / organic vapor cartridge or an clothing, when necessary. bserve good personal hygiene measures, such as washing e eating, drinking, and/or smoking. Routinely wash work

A GMP Metal Parts Protector

Melting point/freezing point Initial boiling point and boiling solvent

Not available. Not available.

Not available.

Not available.

Not available.

-156.0 °F (-104.4 °C) PROPELLANT estimated

Odor

рΗ

range

Flash point Evaporation rate

Odor threshold

Flammability (solid, gas)	Not available.
Upper/lower flammability or explored and the set of the	plosive limits
Flammability limit - lower (%)	0.9 % estimated
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
Specific gravity	0.426 estimated

## 10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents. Nitrates. Fluorine. Chlorine.
Hazardous decomposition products	No hazardous decomposition products are known.

## 11. Toxicological information

## Information on likely routes of exposure

Inhalation	May cause damage to organs through prolonged or repeated exposure by inhalation.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.
Symptoms related to the physical, chemical and toxicological characteristics	Aspiration may cause pulmonary edema and pneumonitis. Dizziness.

#### Information on toxicological effects

Acute toxicity	May be fatal if swallowed and enters airways.		
Components	Species	Test Results	
Butane (CAS 106-97-8)			
Acute			
Inhalation			
LC50	Mouse	1237 mg/l, 120 Minutes	
		52 %, 120 Minutes	
	Rat	1355 mg/l	

Components	Species	Test Results
Naphtha (petroleum), Light Alkylate	e (CAS 64741-66-8)	
Acute		
Dermal		
LD50	Rabbit	> 1900 mg/kg, 24 Hours
Inhalation		
Vapor		
LC50	Rat	> 5000 mg/m3, 4 Hours
		> 4980 mg/m3
		> 4980 mg/m3, 4 Hours
		> 4.96 mg/l, 4 Hours
Oral		
LD50	Rat	4820 mg/kg
Propane (CAS 74-98-6)		
Acute		
Inhalation		
LC50	Mouse	1237 mg/l, 120 Minutes
		52 %, 120 Minutes
	Rat	1355 mg/l
		658 mg/l/4h
* Estimates for product may be	e based on additional component data	a not shown.
Skin corrosion/irritation	Prolonged skin contact may cause t	
Serious eye damage/eye irritation	Direct contact with eyes may cause	
Respiratory or skin sensitization		
Respiratory sensitization	Not a respiratory sensitizer.	
Skin sensitization	This product is not expected to cause skin sensitization.	
Germ cell mutagenicity	No data available to indicate produc mutagenic or genotoxic.	t or any components present at greater than 0.1% are
Carcinogenicity	This product is not considered to be	a carcinogen by IARC, ACGIH, NTP, or OSHA.
IARC Monographs. Overall E	Evaluation of Carcinogenicity	
Not listed. OSHA Specifically Regulated	d Substances (29 CFR 1910.1001-10	050)
Not regulated.		
	gram (NTP) Report on Carcinogens	5
Not listed.	This product is not every stad to source	
Reproductive toxicity	Not classified.	se reproductive or developmental effects.
Specific target organ toxicity - single exposure	Not classified.	
Specific target organ toxicity - repeated exposure	Causes damage to organs through Respiratory system. Eyes. Skin. Kid	prolonged or repeated exposure. Central nervous system. Ineys.
Aspiration hazard	May be fatal if swallowed and enters	s airways.
Chronic effects	Causes damage to organs through	prolonged or repeated exposure.
12. Ecological information		
Ecotoxicity		ironmentally hazardous. However, this does not exclude the Is can have a harmful or damaging effect on the environment.
Persistence and degradability	No data is available on the degrada	bility of this product.
Bioaccumulative potential		
Partition coefficient n-octan		
Butane Mineral Spirits	2.89 3.16	9 6 - 7.15

Propane	2.36	
Mobility in soil	No data available.	
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.	
13. Disposal considerati	ons	
Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.	
Local disposal regulations	Dispose in accordance with all applicable regulations.	
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.	

Waste from residues / unused<br/>productsDispose of in accordance with local regulations. Empty containers or liners may retain some<br/>product residues. This material and its container must be disposed of in a safe manner (see:<br/>Disposal instructions).Contaminated packagingSince emptied containers may retain product residue, follow label warnings even after container is<br/>emptied. Empty containers should be taken to an approved waste handling site for recycling or

#### 14. Transport information

#### DOT **UN number** UN1950 UN proper shipping name Aerosols, flammable, (each not exceeding 1 L capacity) Transport hazard class(es) Class 2.1 Subsidiary risk 2.1 Label(s) Packing group Not applicable. Special precautions for user Read safety instructions, SDS and emergency procedures before handling. **Special provisions** N82 **Packaging exceptions** 306 Packaging non bulk None Packaging bulk None

disposal. Do not re-use empty containers.

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking.

#### ΙΑΤΑ

UN number	UN1950
UN proper shipping name	Aerosols, flammable
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Environmental hazards	No.
ERG Code	10L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed with restrictions.
Cargo aircraft only	Allowed with restrictions.
Packaging Exceptions	LTD QTY
IMDG	
UN number	UN1950
UN proper shipping name	AEROSOLS
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-

A GMP Metal Parts Protector

Label(s)2.1Packing groupNot applicable.Environmental hazardsNo.Marine pollutantNo.EmSF-D, S-USpecial precautions for userRead safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling. Read safety and emergency procedures before handling.Packaging ExceptionsLTD QTYAmsport in bulk according toNot applicable.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code DOT



#### 15. Regulatory information

#### US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

#### TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

#### SARA 304 Emergency release notification

Not regulated.

#### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Hazard categories

#### Superfund Amendments and Reauthorization Act of 1986 (SARA)

Immediate Hazard - Yes Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - Yes Reactivity Hazard - No

#### SARA 302 Extremely hazardous substance

Not listed.

#### SARA 311/312 Hazardous No

chemical

## SARA 313 (TRI reporting)

Not regulated.

#### Other federal regulations

#### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

#### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Butane (CAS 106-97-8) Propane (CAS 74-98-6)

Safe Drinking Water Act Not regulated. (SDWA)

## US state regulations

# US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

## US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd.

(a))

Butane (CAS 106-97-8) Mineral Spirits (CAS 8052-41-3) Naphtha (petroleum), Light Alkylate (CAS 64741-66-8)

#### US. Massachusetts RTK - Substance List

Butane (CAS 106-97-8) Mineral Spirits (CAS 8052-41-3) Propane (CAS 74-98-6)

#### US. New Jersey Worker and Community Right-to-Know Act

Butane (CAS 106-97-8) Propane (CAS 74-98-6)

#### US. Pennsylvania Worker and Community Right-to-Know Law

Butane (CAS 106-97-8) Mineral Spirits (CAS 8052-41-3) Propane (CAS 74-98-6)

#### US. Rhode Island RTK

Butane (CAS 106-97-8) Propane (CAS 74-98-6)

#### US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

#### International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

### 16. Other information, including date of preparation or last revision

Issue date	06-26-2018
Version #	01

Disclaimer	The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.
Revision information	Product and Company Identification: Alternate Trade Names