



Revision Date: 05/19/2015

Section 1 Identification

DOOM II Trade Name: Product Identification: A561

Synonyms: Solvent blend

Product UseDescription:

Herbicide

General Info Phone: (800) 548-2080 Emergency Phone: (800) 255-3924

Supplier:

General Products & Supply, Inc.

101 Technology Lane Export, PA 15632

Section 2 Hazards Identification

Classifications

Flammable Aerosols - Category 1

Gasses under pressure - Liquefied gas

Aspiration Hazard - Category 1

Carcinogenicity - Category 2

Germ Cell mutagenicity - Category 2

Eye Irritation - Category 2

Skin Irritation - Category 2

Skin Sensitization - Category 1

Specific Target Organ Toxicity (single exposure) - Category 3







Flammable

Compressed Gas

Irritant

Heatlh Hazard

Signal Word: Danger

Hazard Statements

Keep out of reach of children.

Read label and SDS before use.

Suspected of causing cancer

Suspected of causing genetic defects.

May cause respiratory irritation

May cause drowsiness or dizziness.

Causes serious eye damage and skin irritation.

May cause an allergic skin reaction

May be fatal if swallowed and enters airways.

Extremely flammable aerosol

Contains gas under pressure; may explode if heated.

Precautionary Statements

Prevention

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Avoid breathing fumes/mists

Wash hands thoroughly afterhandling.

Use only outdoors or in a well-ventilated area.





A561 DOOM II

Wear protective gloves.

Wear eye or face protection.

Contaminated clothing must not be allowed out of the workplace.

Keep away from heat, sparks, open flames and hot surfaces. - -No

smoking. Do not spray on an open flame or other ignition source.

Pressurized container: Do not pierce or burn, even after use.

Do not eat, drink or smoke when using this product.

Response

IF SWALLOWED: Immediately call a poison center. Do NOT induce vomiting.

IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs get medical attention.

Take off contaminated clothing and wash before reuse.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Immediately call a poison center or a physician

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a poison center or doctor if you feel unwell.

If EXPOSED or CONCERNED: Get medical attention.

Storage

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Store locked up in a well-ventilated place. Keep cool.

Disposal

Dispose of contents and container in accordance with all local, regional, and national regulations.

Hazards Not Otherwise Specified

Not applicable

Section 3 Composition

		Concentration
Chemical Name	CAS#	% by Weight
Fuels, diesel, no. 2	68476-34-6	>=75 <= 85
Solvent naphtha, petroleum, heavy aromatic	64742-94-5	>=10 <= 15
Carbon Dioxide	124-38-9	>=1 <= 5
Diethylene Glycol Ethyl Ether	111-90-0	>=1 <= 5
Isooctyl (2-ethylhexyl) Ester of 2,4-D	1928-43-4	=1.09
Bromacil	314-40-9	=0.98
Naphthalene	91-20-3	<= 1

Section 4 First Aid





EMERGENCY OVERVIEW

DANGER. Extremely flammable. Contents under pressure. Harmful or fatal if swallowed. Aspiration hazard if swallowed. Vapor harmful. Keep away from heat and flame. Can cause nervous system depression.

EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

SKIN: Wash with plenty of soap and water. If skin irritation occurs get medical attention. Take off contaminated clothing and wash it before reuse.

INHALATION: Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell

INGESTION: Harmful or fatal if swallowed. Seek medical attention immediately. Aspiration hazard - this material can enter lungs during swallowing or vomiting and cause lung inflammation and damage.

Section 5 Fire Fighting Measures

Suitable fire extinguishing media:

Use water spray, fog or foam.

Specific hazards arising from the chemical:

Flammable aerosol. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of subsequent explosion. Gas may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back, causing fire or explosion. Bursting aerosol containers may be propelled from a fire at high speed. Runoff to sewer may create fire or explosion hazard.

Hazardous thermal decomposition products:

Carbon Dioxide, Carbon Monoxide

Specific fire-fighting methods:

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire fighters:

Fire fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in a positive pressure mode.

Section 6 Accidental Release Measures





Personal precautions:

Put on appropriate personal protective equipment (see section8)

Environmental precautions and clean-up methods:

Stop all leaks. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Eliminate all ignition sources. Disperse vapors with water spray. Prevent runoff from entering drains, sewers, streams or other bodies of water. Absorb spill with inert material. Absorb unrecoverable product. Transfer contaminated absorbent, soil and other materials to containers for disposal.

Section 7 Handling and Storage

Do not get in eyes, on skin or on clothing. Avoid breathing sprays and vapors. Avoid skin contact. Keep out of reach of children.

Do not use or store near heat, sparks or open flame. Exposure to temperatures above 120 F may cause bursting. Do not puncture or incinerate container. Store in a cool, dry place. Intentional misuse by deliberately concentrating and inhaling may be harmful or fatal. Keep out of reach of children.

Section 8 Exposure Controls/Personal Protection

Carbon Dioxide

ACGIH TLV 800 ppm

Diethylene Glycol Ethyl Ether

ACGIH TLV 25 ppm OSHA PEL 25 ppm

Fuels, diesel, no. 2

ACGIH TLV 100 mg/m3

Isooctyl (2-ethylhexyl) Ester of 2,4-D

ACGIH TLV 10 mg/m3 OSHA PEL 10 mg/m3

Naphthalene

ACGIH TLV 10 ppm OSHA PEL 10 ppm

Eye Protection: Wear safety glasses or goggles.

Skin Protection: To prevent repeated or prolonged contact, wear impervious gloves (made from rubber, nitrile or neoprene).

Respiratory Protection: When respiratory protection is required use an organic vapor cartridge. A respiratory program that

meets OSHA's 29 CFR 1910.34 & ANSI Z88.2requirements must be followed.

Engineering Controls: Good general ventilation required.

Section 9 Physical and Chemical Properties





<u>Property</u> <u>Value</u>

Appearance CLEAR LIQUID Auto Ignition Temp NOT AVAILABLE

Boiling Point NOT AVAILABLE Color YELLOW

Decomposition Temperature NOT AVAILABLE Evaporation Rate NOT AVAILABLE NOT AVAILABLE Explosive Properties NOT AVAILABLE Explosive Limit Ranges Flash Point 125 F (liquid portion) Melting/Freezing Point NOT AVAILABLE Odor Odor Threshold SOLVENT NOT AVAILABLE

Other Information VOC content (wt. %): 80 Oxidizing Properties NOT AVAILABLE

Partition Coeff NOT AVAILABLE Physical State LIQUID
Relative Density 0.8 Solubility (Water) INSOLUBLE

Vapor DensityNOT AVAILABLEVapor PressureNOT AVAILABLEViscosityNOT AVAILABLEpHNOT APPLICABLE

Section 10 Stability and Reactivity

Reactivity: Under normal conditions of storage and use, hazardous reactions will not occur.

Chemical Stability: Stable under normal conditions.

Incompatible Materials: Acids, strong oxidizers.

Conditions to Avoid : High temperatures, open flames, sparks, welding.

Decomposition Products: CO, CO2

Vapors may ignite at temperatures exceeding flash point.

Section 11 Toxicological Information

Primary Route of Entry: Skin contact, inhalation, ingestion

Acute/Potential Health Effects:

EYES: May cause serious eye irritation. Symptoms include stinging, tearing and redness.

SKIN: May cause skin irritation. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, drying of skin and skin burns.

INHALATION: High vapor/aerosol concentrations (>1000 ppm) are irritating to the eyes and respiratory tract. May cause headaches, dizziness, anesthesia, drowsiness, unconsciousness, and other central nervous system effects, including death. May cause peripheral nervous system disorder and/or damage.

INGESTION: Harmful or fatal if swallowed. Aspiration hazard - this material can enter lungs during swallowing or vomiting and cause lung inflammation and damage.

Chronic / Long Term Effects: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Signs and Symptoms of Overexposure: Signs and symptoms of overexposure to this material through breathing, swallowing, and/or passage of material through the skin may include: stomach or intestinal upset (nausea vomiting, diarrhea) irritation (nose, throat, airways), central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness).

Target Organ Effects: Central nervous system, skin.

Reproductive/Developmental Information: Suspected genetic cell mutagen.

Carcinogenic Information: Diesel fuel: ACGIH - A3; Naphthalene: NTP - Possible Select Carcinogen, IARC - Group 2B

WARNING: This product contains chemicals known to the State of California to cause cancer.

Acute Toxicity Values:

Bromacil: Oral LD50 (rat) 1723 mg/kg; 2,4-D Oral LD50 (rat) 896 mg/kg.





Section 12 Ecological Information

2,4-D: 96-hour LC50 Rainbow Trout: 7.2 mg/l. Bromacil: 96-hour LC50 Rainbow Trout: 38 ppm.

Section 13 Disposal Considerations

Waste must be disposed of in accordance with federal, state and local environmental control regulations. See label for further instructions.

Section 14 Transport Information

Certain shipping modes or package sizes may have exceptions from the transport regulations. The classification provided may not reflect those exceptions and may not apply to all shipping modes or package sizes.

UN number 1950

Proper shipping name Aerosols, flammable

Class 2.1 Packing group

.

Section 15 Regulatory Information

California Proposition 65 (Safe Drinking Water and Toxic Enforcement Act)

Naphthalene

CERCLA RQ (40 CFR 302)

Naphthalene 100 lbs

Section 313 of Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 (40 CFR 372.65)

Diethylene Glycol Ethyl Ether Isooctyl (2-ethylhexyl) Ester of 2,4-D

Bromacil Naphthalene

If identified components of this product are CERCLA hazardous substances and/or listed under Sections 302, 304, or 313 of

<u>Title III</u> of the Superfund Amendments and Reauthorization Act (SARA) of 1986 (also known as EPCRA, the Emergency Planning and Community Right-To-Know Act), or under <u>California Proposition 65</u> (Safe Drinking Water and Toxic Enforcement Act), they are listed above in Section 15 of this SDS.

If identified components of this product are listed under Section 313, this product contains toxic chemicals subject to the reporting requirements of Section 313. This information must be included in all SDS that are copied and distributed for this material.

Title III Section 311/312 Hazardous Categories - 40 CFR 370.2:

ACUTE (X) Chronic (X) Fire (X) Pressure (X) Reactive () Not Applicable ()

<u>T.S.C.A. Status:</u> All chemical substances found in this product comply with the Toxic Substances Control Act inventory reporting requirements.

<u>RCRA Status:</u> Under RCRA, it is the responsibility of the product user to determine at the time of disposal, whether a material containing the product or derived from the product should be classified as a hazardous waste. If this product becomes hazardous waste it would be assigned RCRA Code(s)





D001, D016

FIFRA information

This chemical is a pesticide product registered by the United States Environmental Protection Agency and is subject to certain labeling requirements under federal pesticide law. These requirements differ from the classification criteria and hazard information required for safety data sheets (SDS), and for workplace labels of non-pesticide chemicals. The hazard information required on the pesticide label is reproduced below. The pesticide label also includes other important information, including directions for use.

Signal word: CAUTION. Hazard statement: Harmful if absorbed through skin. Harmful if inhaled.

Section 16 Other Information

HMIS Ratings:



Disclaimer: This Manufacturer believes that the information contained in the Safety Data Sheet is accurate. The suggested procedures are based on experience as of the date of the publication. They are not necessarily all inclusive nor fully adequate in every circumstance. Also, the suggestions should not be confused with, nor followed in violation of applicable laws, regulations, rules or insurance requirements.

Preparation/Revision Date: 5/19/15