

QUICK SEAL is ideal for use wherever a strong, permanently elastic, weatherproof adhesive, sealant, or caulk is needed. This product has excellent adhesion characteristics, high chemical resistance and will not sag or shrink due to severe temperature extremes.

QUICK SEAL can be used for sealing cracks in machinery, heating and ventilating duct work, plumbing fixtures, electrical connections, low pressure water and drain pipes. This product bonds nameplates, machinery flanges, glass, signs and electrical insulation, etc. Ideal for caulking windows, doors, walls, ceiling cracks and crevices. Forms in-place gaskets. Paint will not adhere to cured material.

This product meets Federal Specs TT-S-001543A (COM-NBS) TT00230C COM-NBS).

Not recommended for use on cylinder heads, intake/exhaust manifolds, carburetors, or continuous immersion in gasoline.

DIRECTIONS

For best adhesion, surface must be clean, dry, and free of oil, tar, dirt and dust. A 1/16" to 1/8" bead dries in one hour, cures in 24 hours and reaches optimum strength in 7 days.

Leave a small bed of material on the can, which will form a sealing plug, for reuse. To use, gently pull the plug and begin to use the material. If plug breaks, leaving the dispensing tip sealed, use a paper clip or other wire object to remove and loosen the remainder of the cured material.

Contains: Dimethylsiloxane (CAS #70131-67-8) Amorphous Silica (CAS #7631-86-9), Methyltriacetoxysilane (CAS #4253-34-3), Ethyltriacetoxysilane (CAS #17689-77-9)



GENERAL MAINTENANCE PRODUCTS

QUICK SEAL CLEAR
Silicone Sealer
Caulker-Adhesive

- 100% RTV Silicone, Industrial Strength
- Temperature Range -60°F to +500°F
- Caulks Around Tubs, Sinks And Showers
- Insulated Electrical Components
- Seals Around Windows, Doors, Walls, Etc.
- Bonds Most Materials, Similar Or Dissimilar (Glass, Wood, Metal, Rubber, Plastic, Ceramics, etc.)
- Mildew Resistant Formula

KEEP OUT OF REACH OF CHILDREN
NET CONTENTS: 7.25 oz (205 g)

CAUTION
Contact with uncured sealant causes irritation. Contents under pressure. Outer container is pressurized with a flammable hydrocarbon propellant. Do not remove rubber plug. Product releases acetic acid (vinegar-like odor) during curing. Contact lens wearers take appropriate precautions.

FIRST AID
In case of contact with skin, wipe off excess sealant with dry paper towel or cloth, and wash with soap and water. In case of eye contact, immediately flush with water for 15 minutes. CALL A PHYSICIAN IMMEDIATELY.

KEEP OUT OF REACH OF CHILDREN



Reorder A591
800-548-2080

HMIS RATING
1 - FLAMMABILITY
1 - HEALTH
0 - REACTIVITY
B- PERSONAL PROPERTY

SOLD EXCLUSIVELY BY:


General Products & Supply Inc.



Murrysville Business Park
Export, PA 15632

101 Technology Lane
(800) 548-2080