

**QUICK GASKET BLACK** can be used on metal, glass, ceramics, wood, rubber and most plastics. As an instant gasket maker, this product replaces a wide range of cork, paper, asbestos, felt and metal gaskets. **QUICK GASKET BLACK** has excellent adhesion characteristics and high chemical resistance, will not sag or shrink, and is impervious to temperature extremes.

**QUICK GASKET BLACK** forms gaskets in place for oil and transmission pans, oil and water pumps, valve and timing chain covers, gear boxes, compressors, machine covers, and electric motors and electrical control boxes.

## DIRECTIONS

For best adhesion, surface must be clean, dry and free of oil, tar, dirt and dust. Hold the can at a 45° angle and apply a continuous bead of 1/16" to 1/8" to the mating surface, encircling all boltholes. For adhesion to both parts, assemble immediately. For one part adhesion, allow 10 to 15 minutes for bead to skin. Assemble the parts, but do not squeeze gasket out by over tightening the bolts. This product starts to cure immediately and fully cures in 24 hours. Optimum strength is reached in 7 days.

Leave a small bead of material on the can, which will form a sealing plug, for reuse. To use, gently pull the plug and begin to use the material. If the plug breaks leaving the dispensing tip sealed, use a paper clip or other wire object to remove and loosen the remainder of the cured material.

**QUICK GASKET BLACK** is not recommended for use on cylinder heads, exhaust or intake manifolds, carburetors or continuous immersion in gasoline.

CAS Numbers: Contains Polymer (70131-67-8), Silica (7631-86-9), Carbon Black (1333-86-4), Methyl Triacetoxysilane (4253-34-3), Ethyl Triacetoxysilane (17689-77-9).

**Gmp**  
Chemical Solutions

A593

## GENERAL MAINTENANCE PRODUCTS

### QUICK GASKET BLACK Hi-Temperature Silicone Gasket Maker

- Reduces Inventory, Eliminates Need To Stock Conventional Gaskets
- 100% RTV Silicone, Industrial Strength
- Reduces Down Time, Gets Equipment Back In Operation Fast
- Pressurized Dispensing Makes Any Size Or Shape Gasket Instantly
- Remains Permanently Flexible, Temperature Range -60°F To +500°F

**CAUTION:** On contact, uncured sealant causes irritation. Avoid contact with eyes and skin. See additional precautions on side panel.

**KEEP OUT OF REACH OF CHILDREN**  
**NET CONTENTS 8 OZ(S)**

## CAUTION

On contact, uncured sealant causes irritation. Avoid contact with eyes and skin. Contact lens wearers take appropriate precautions. Sealant releases acetic acid (vinegar-like odor) during cure. Contents under pressure. Do not puncture or incinerate. Do not store at temperatures above 120°F.

## FIRST AID

**IF IN EYES:** Flush with plenty of water. Contact a physician.

**IF ON SKIN:** Remove from affected area with a dry cloth or paper towel. If irritation persists, contact a physician.

**IF INHALED:** Give oxygen. If irritation persists, seek medical attention.

**IF SWALLOWED:** Do not induce vomiting. Contact a physician.

## KEEP OUT OF REACH OF CHILDREN



Reorder A593  
800-548-2080

### HMIS RATING

1 - FLAMMABILITY

1 - HEALTH

0 - REACTIVITY

B - PERSONAL PROPERTY

SOLD EXCLUSIVELY BY:

  
General Products & Supply Inc.

**Gmp**  
Chemical Solutions

Murrysville Business Park  
Export, PA 15632

101 Technology Lane  
(800) 548-2080