

LITH-A-WHITE is used on bearings, slides, rollers, chains, small gears, linkages, hinges, tools, cranks, sprockets and over-head tracks. **LITH-A-WHITE** is heat resistant to 350°F and sprays liquid-air, which cures to a thick grease. It is resistant to water washout and prevents rust and corrosion. Outstanding tenacity – clings to metal and will not run.

Contains
NO Chlorinated Solvents
(NO 1,1,1-Trichloroethane)
NO Hexane • No CFC's

USE FOR:

Auto doors, hoods and trunk lids, gears, chains, sprockets, linkages, slides, bearings, hinges, cranks, pinions, worms, overhead door tracks and rollers.

DIRECTIONS

SHAKE WELL BEFORE USING

Spray on a clean, dry surface from a distance of 6 to 8 inches. Insert extension tube into actuator orifice for pinpoint application. Tube package included in carton. Repeat application periodically.



GENERAL MAINTENANCE PRODUCTS



DANGER: Contains Isoparaffinic Hydrocarbon (64741-66-8), Lithium Grease (N/A), and Liquified Petroleum Gas (68476-85-7). Use only in a well ventilated area. Do not use near heat, sparks or open flame. Avoid contact with eyes or prolonged contact with skin. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F.

FIRST AID

EXCESSIVE INHALATION: Remove to fresh air and call a physician.

IF SWALLOWED: Do not induce vomiting. Get medical attention.

IF EYE CONTACT: Flush with water for 15 minutes, lifting upper and lower lids. Get medical attention.

IF SKIN CONTACT: Wash affected area immediately with soap and water. If irritation persists, get medical attention.

KEEP OUT OF REACH OF CHILDREN



HMIS RATING
2 - FLAMMABILITY
1 - HEALTH
0 - REACTIVITY
B - PERSONAL PROPERTY

SOLD EXCLUSIVELY BY:

General Products & Supply Inc.

GMP
 Chemical Solutions

Murrysville Business Park
 Export, PA 15632

101 Technology Lane
 (724) 327-7200