

**SAFETY SEAL** is a slip-resistant, epoxy coating that cures to a hard, flat, textured finish. Designed for interior and exterior use on concrete, steel, wood, fiberglass, aluminum and other surfaces where a slip-resistant finish is desired.

**EFFECTIVE ON:** Steps, ramps, loading docks, ladders, running boards, showers, bathtubs, around machinery or anywhere water or other slippery conditions exist.

**SURFACE PREPARATION:** The surface should be dry, clean and free of oil, wax, dirt, loose paint and/or other contaminants. Previously painted surfaces should be cleaned with a mild cleaner, rinsed and dried.

Before initial application to surface, a light etch or sanding is recommended. Test a small area for compatibility and adhesion. The coating is self-priming on most surfaces.

**DRY TIME:** Dries to touch in approximately one hour. Make sure first coat is dry before applying second coat. The rate of cure will vary with the film thickness, temperature and humidity. Wait 24 hours before subjecting to heavy foot traffic. Application will continue to cure for several days. Recoat every 3 to 6 months depending on wear.

**USE DIRECTIONS:** For best results apply with ambient temperatures between 60°F to 90°F. Shake can until ball rattles freely and then for an additional 60 seconds. Epoxy must be mixed well before and during use to achieve the correct color and texture. For best results, shake can periodically during use. Spray in a sweeping motion at a distance of 12 to 15 inches from area to be treated.

**IMPORTANT:** To prevent clogging; after each use, invert can and spray a few short bursts to clear valve.



## GENERAL MAINTENANCE PRODUCTS



**DANGER:** Contains Acetone (67-64-1), Epoxy Resin (Proprietary), Toluene (108-88-3), Xylene (1330-20-7), Propane (74-98-6), Butane (106-97-8), Isobutane (75-28-5), Ethyl Benzene (100-41-4). May also contain Amorphous Fumed Silica (112945-52-5), D&C Orange No. 17 (3468-63-1). VAPOR HARMFUL. MAY AFFECT THE BRAIN OR NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE, OR NAUSEA. CAUSES SKIN, NOSE AND THROAT IRRITATION. MAY CAUSE ALLERGIC SKIN REACTION. MAY BE HARMFUL IF ABSORBED THROUGH THE SKIN. Do not puncture or incinerate (burn) container. Exposure to heat or prolonged exposure to sun may cause bursting. Do not expose to heat or store at temperatures above 120°F.

**NOTICE:** Repeated and prolonged exposure to solvents may cause permanent brain and nervous system damage. May cause liver and kidney damage. In addition, inhaling the concentrated contents is harmful and may be fatal.

**Vapor may ignite explosively.** Keep away from heat, sparks, and flame. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation.

**Use only with adequate ventilation.** Do not breathe vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Failure to wear proper respiratory protection may result in permanent brain and nervous system damage. Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling.

**WARNING:** This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

**FIRST AID:** In case of eye contact, flush immediately with plenty of water, lifting eyelids occasionally, for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. If swallowed, do not induce vomiting. Call a physician immediately.

**KEEP OUT OF REACH OF CHILDREN**  
SAFETY SEAL 80% VOC



BUY USA

Reorder A800  
800-548-2080

HMIS RATING
4 - FLAMMABILITY
2 - HEALTH
0 - REACTIVITY
1 - PERSONAL PROPERTY

SOLD EXCLUSIVELY BY:

  
General Products & Supply Inc.

  
GMP  
Chemical Solutions

Murrysville Business Park  
Export, PA 15632

101 Technology Lane  
(800) 548-2080