

www.generalproductsdirect.com

GMP Engineered Maintenance Unit of Solutions

Safety Data Sheet (S.D.S.)

Safety Data Sheet (SDS)

Section 1 - Chemical Product and Company Information

TELEPHONE: 724-327-7200

PRODUCT NAME: MEGACLEAN

RECOMMENDED USE:

VOC compliant parts cleaner **RESTRICTIONS ON USE:**

FAX: 724-325-4522

PA 15632

For intended use only

ITEM NUMBER: C362

EMERGENCY CONTACT (spill/release): 800-255-3924

Section 2 - Hazards

According to Regulation 2012 OSHA Hazard Communication Standard: 29 CFR Part 1910.1200

GHS Ratings:

Aspiration hazard

Aspiration Toxicity Category 1: Known (regarded)- human evidence - hydrocarbons with kinematic viscosity ? 20.5 mm2/s at 40° C.

SOLD BY: General Products & Supply, Inc. 101 Technology Lane, Export,

GHS Hazards

H304

May be fatal if swallowed and enters airways

1

GHS Precautions

P331	Do NOT induce vomiting
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
P405	Store locked up
P501	Dispose of contents/container in accordance with local/ regional/ national/, regulations.

Signal Word: Danger



Section 3 - Composition		
Chemical Name	CAS number	Weight Concentration %
Distillates (petroleum), hydrotreated light	64742-47-8	90.00% - 100.00%

Section 4 - First Aid Measures

INHALATION - Take affected persons out into the fresh air. Supply fresh air; consult doctor in case of complaints.

Provide oxygen treatment if affected person has difficulty breathing.

In case of irregular breathing or respiratory arrest provide artificial respiration.

In case of unconsciousness place patient stably in side position for transportation.

EYE CONTACT - In case of eye contact, flush the eyes with water for fifteen (15) minutes. If contact lenses are worn, quickly remove them, then flush the eyes with water. Have a physician examine the eyes.

SKIN CONTACT - Immediately remove any clothing soiled by the product. Immediately wash with water and soap and rinse thoroughly. If skin irritation continues, consult a doctor.

INGESTION - If material is ingested, seek immediate medical attention. If vomiting occurs spontaneously, keep the head below the hips to prevent aspiration of liquid into the lungs.

Notes to Physician: If swallowed, gastric irrigation with added, activated carbon.

If swallowed or in case of vomiting, danger of entering the lungs.

If necessary oxygen respiration treatment.

Section 5 - Fire Fighting Measures

Flash Point: 95 C (203 F) LEL: N/A

UEL: N/A

EXTINGUISHING MEDIA: Use carbon dioxide (CO2), "alcohol" foam, dry chemical, or sand.

UNUSUAL FIRE OR EXPLOSION HAZARDS: The product vapor is heavier than air and may travel a considerable distance to a source of ignition and flashback.

HAZARDOUS COMBUSTION PRODUCTS: See section 10 for a list of hazardous decomposition products for this mixture.

FIRE FIGHTING: If evacuation of personnel is necessary, evacuate to an upwind area. Decontaminate personnel and equipment with a water wash-down after fire and smoke exposure.

FIRE FIGHTING EQUIPMENT: Firemen and emergency responders: wear full turnout gear or Level A equipment, including positive-pressure, self-contained breathing apparatus (SCBA).

Section 6 - Accidental Release Measures

SPILL AND LEAK PROCEDURES: Spill supervisor - Ensure cleanup personnel wear all appropriate Personal Protective Equipment (PPE), including respiratory protection. Remove all ignition sources. Keep nonessential

personnel away from the contaminated area.

SMALL SPILLS: Ventilate the contaminated area. Using nonsparking tools, mix the appropriate sorbent into the spilled material. Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Collect the saturated sorbent and transfer it into a covered container. Steel containers are acceptable for all wastes except wastes which contain acid. Use suitable plastic containers for acid-bearing wastes.

Dispose of the waste in compliance with all Federal, state, regional, and local regulations.

LARGE SPILLS: Prevent this material from entering sewers and watercourses by diking or impounding the spilled material. Advise authorities if the product has entered or may enter, sewers, watercourses, or extensive land areas.

Ventilate the contaminated area. Using nonsparking tools, mix the appropriate sorbent into the spilled material. Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Collect the saturated sorbent and transfer it into a covered container. Steel containers are acceptable for all wastes except wastes which contain acid. Use suitable plastic containers for acid-bearing wastes.

Label the waste container. Dispose of the waste in compliance with all Federal, state, regional, and local regulations.

Section 7 - Handling and Storage

HANDLING PRECAUTIONS: Wear all appropriate Personal Protective Equipment (PPE). Wear respiratory protection or ensure adequate ventilation at all times as vapors can accumulate in confined or poorly ventilated areas. Use the product in a manner which minimizes splashes and/or the creation of dust. Keep containers closed when not in use. Do not handle or store material near heat, sparks, open flames, or other sources of ignition. Store at room temperatures, i.e., 40 to 95 F (4 to 35 C).

STORAGE: Requirements to be met by storerooms and receptacles:

Store in a cool location. Provide ventilation for receptacles. Avoid storage near extreme heat, ignition sources or open flame. • Information about storage in one common storage facility: Store away from foodstuffs. Store away from oxidizing agents. Do not store together with acids. • Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles. Keep container tightly sealed.

REGULATORY REQUIREMENTS: No data found.

Section 8 - Exposure Controls / Personal Protection				
Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits	
Distillates (petroleum), hydrotreated light 64742-47-8	Not Established	TLV (US, 4/2014), Absorbed through skin, TWA: 200 mg /m3, 8 hours, (as total hydrocarbon vapors)	Not Established	

ENGINEERING: Do not use near fire or flame.

VENTILATION: Use only with adequate ventilation, i.e., ventilation in compliance with occupational exposure limits. Use mechanical ventilation to reduce buildup of vapors in enclosed areas.

ADMINISTRATIVE CONTROLS: Read SDS and follow recommended procedures.

PROTECTIVE EQUIPMENT: Wear splash goggles. If extra protection is required, wear a face shield over the splash goggles. Face shields are effective only if worn in addition to splash goggles.

Wear a chemical-resistant, butyl-rubber apron and other protective clothing, as deemed appropriate, to avoid skin contact with material.

Wear chemical-resistant gloves (butyl rubber or neoprene). Protective gloves should be inspected frequently and discarded when they exhibit cuts, tears, pinholes, or signs of excessive wear.

Respiratory protection may not be needed if the local exhaust is sufficient to maintain levels of hazardous ingredients below occupational exposure limits. If needed, use a NIOSH/MSHA approved respirator equipped with a full facepiece, organic vapor cartridges, and high-efficiency, particulate air (HEPA) filters. Do not use respirators beyond their capabilities. FOR EMERGENCIES AND UNKNOWN CONCENTRATIONS, use supplied-air respiratory protection or a positive-pressure, self-contained breathing apparatus (SCBA).

CONTAMINATED EQUIPMENT: Dispose of the waste in compliance with all Federal, state, regional, and local regulations.

Section 9 - Physical and Chemical Properties

This mixture typically exhibits the following properties under normal circumstances:

Appearance: Clear liquid	Odor: Mild hydrocarbon
Vapor Pressure: 0.027 kPa @ RT	Odor threshold: No Data
Vapor Density: 4.5	pH: No Data
Specific Gravity: 0.804	Melting point: No Data
Freezing point: No Data	Solubility: No Data
Boiling range: 223 - 245°C	Flash point: 203°F,95°C
Evaporation rate: No Data	Flammability: No Data
Explosive Limits: N/A	Partition coefficient No Data (n-octanol/water):
Autoignition temperature: No Data	Decomposition temperature: No Data
Viscosity: No Data	Grams VOC less water: No Data

Section 10 - Stability and Reactivity

Stability: Hazardous polymerization will not occur.

STABLE

Components of this mixture are incompatible with the following materials: Oxidizers. This mixture may soften certain

This mixture is likely to exhibit the following combustion products: Oxides of carbon and nitrogen

Hazardous polymerization will not occur.

Section 11 - Toxicological Information

Mixture Toxicity

Dermal Toxicity LD50: 2,001mg/kg

Component Toxicity

64742-47-8 Distillates (petroleum), hydrotreated light Dermal LD50: 2,001 mg/kg (Rabbit)

Exposure to this material may affect the following organs:

Effects of Overexposure

 Carcinogenicity:
 The following chemicals comprise 0.1% or more of this mixture and are listed and/or classified as carcinogens or potential carcinogens by NTP, IARC, OSHA (mandatory listing), or ACGIH (optional listing).

 CAS Number
 Description
 % Weight
 Carcinogen Rating

Preexisting skin, eye, and respiratory disorders may be aggravated by exposure to this product. .

Section 12 - Ecological Information

Ecological information: No data found.

Component Ecotoxicity

Section 13 - Disposal Considerations

As the US EPA, state, regional, and other regulatory agencies may have jurisdiction over the disposal of your facility's hazardous waste, it is incumbent upon you, the hazardous waste generator, to learn of and satisfy all the requirements which affect you. Dispose of the hazardous waste at a properly licensed and permitted disposal site or facility. Ensure conformity to all applicable hazardous waste disposal regulations.

The US EPA Hazardous Waste Numbers which follow are applicable to this unadulterated product if the product enters the "waste stream." Refer to Title 40 of the Code of Federal Regulations, Part 261 (40 CFR 261). This part of the Code identifies solid wastes which are subject to regulation under various sections of the Code and which are subject to the notification requirements of Section 3010 of the Resource Conservation and Recovery Act (RCRA).

Section 14 - Transport Information

This material is classified for transport as follows:

Agency	Proper Shippin
US DOT	Non Regulated

<u>ng Name</u>

UN Number Packing Group **Hazard Class**

Non Regulated

Section 15 - Regulatory Information

Additional regulatory listings, where applicable.

Country Canada US **EU Risk Phrases**

Regulation Canadian Domestic Substances List Toxic Substances Control Act

All Components Listed Yes Yes

Safetv Phrase

Toxic Substances Control Act (TSCA): All chemicals except those listed below appear in the Toxic Substances Control Act Chemical Substance Inventory:

- None

Section 16 - Other Information

Hazardous Material Information System (HMIS)

National Fire Protection Association (NFPA)



DISCLAIMER AND NON-WARRANTY: This Safety Data Sheet was prepared by Shore Corporation and is correct to the best of our knowledge, information and belief at the date of its publication. The information came from raw material suppliers, regulatory databases, and/or third parties with expertise in this area. This information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release. No warranties of any kind, either expressed or implied, including warranties of the accuracy of the information presented and the suitability of a product for a particular purpose.

Date revised: 2021-06-25 Date Prepared: 6/25/2021 **Reviewer Revision**