TRICHLOR-JUB is a fast-drying blend of nonflammable petroleum solvents formulated for the removal of grease, oil, wax, ink, lint, dust, mold release agents, some adhesives, and light carbon deposits.

TRICHLOR-JUB may be used to clean and degrease electric motors, automatic pinsetters, printed circuits, sewing machines, textile industry machines, printing presses, rollers, blankets, offset type, watch and clock parts, radio and television components, precision parts, condensers and coils, generators and starters, electrical and mechanical equipment, typewriters and other office machines.

With the use of **TRICHLOR-SUB** for regular maintenance and protection, fire hazards and losses are reduced, motor life is extended, equipment downtime is reduced, and repair and replacement costs are minimized.

DIRECTIONS

General degreasing: spray on and blow dry, spray on and wipe off, wipe on with a brush or rag, or use an immersion cleaner and air dry parts. Wire brush and/or repeat application as necessary or appropriate. Product may be transferred to pressure sprayer if desired. Check to be sure all materials are solvent resistant before allowing product to be transferred to any container.

Electric motors: motors may be cleaned and degreased while in operation by spraying solvent into openings. Smaller motors may be cleaned by immersion. After cleaning is accomplished, motor should be blown dry with compressed air and relubricated to protect bearings.

CAS Numbers: aliphatic petroleum distillate (8052-41-3), 1-bromopropane (106-94-5).

ATTENTION

This product is safe for use on a wide variety of plastics including most used in contact and circuit board construction. However, it may affect certain types of plastics such as PVC, ABS, styrenes, polycarbonates, and more. If unsure of material construction or compatibility, always test in an inconspicuous area prior to use.



GENERAL MAINTENANCE PRODUCTS

TRICHLOR-SUB Industrial Safety Solvent

- Non-flammable/fast drying
- Noncorrosive and nonetching
- Does not deplete the Ozone
- Ready to Use
- No residue
- 41,000 volt dielectric constant

CAUTION: Vapor harmful. Harmful or fatal if swallowed. Eye and skin irritant. See additional precautionary information on side panel.

KEEP OUT OF REACH OF CHILDREN NET CONTENTS 5 GAL(S)

CAUTION

Vapor may be harmful. May irritate respiratory tract. Use with adequate ventilation. Avoid prolonged or repeated breathing of vapors. Harmful or fatal if swallowed. Do not take internally. Eye and skin irritant. Avoid contact with skin and eyes. Avoid contamination of food.

Container disposal: triple rinse container and discard according to local regulations.

FIRST AID


IF IN EYES: Flush with water for at least 15 minutes. If irritation persists, contact a physician.

IF ON SKIN: Remove contaminated clothing. Wash with soap and warm water. If irritation persists, consult a physician.

IF INHALED: Remove to fresh air. Resuscitate if necessary. Get medical attention.

IF SWALLOWED: Do not induce vomiting. Call physician immediately.

KEEP OUT OF REACH OF CHILDREN



SOLD EXCLUSIVELY BY:





Murrysville Business Park Export, PA 15632 101 Technology Lane (724) 327-7200