SURE-SLIDE is an asphalt coating formulated to prevent asphalt from sticking to truck beds, pavers, and equipment. Because of its silicone compound base, **SURE-SLIDE** is environmentally friendly and totally biodegradable. Soil contamination problems are eliminated as associated with diesel fuel now on watch by the EPA. **SURE-SLIDE** makes clean up easy and saves downtime normally used for cleaning.

DIRECTIONS

Apply **SURE-SLIDE** with **GMP** 3-gallon poly compression sprayer at an even rate on all surfaces that would have contact with asphalt. Make certain surface is clean of any bituminous or asphalt deposits before coating any surface. Spray two coats liberally if time allows. Allow five minutes between coats. Make certain re-spray at the conclusion of each workday or between loads if possible. Use **GMP CITRA-SOLVE**, specialty emulsifier, for bituminous deposits at the end of the workday for total clean up.

CAS Numbers: Contains 2-butoxyethanol (111-76-2), aminoethylaminopropylpolysiloxane (68554-54-1), nonionic surfactant (9016-45-9), xanthan gum (11138-66-2)



C139

GENERAL MAINTENANCE PRODUCTS

SURE-SLIDE

Asphalt Release Coating

- Stops asphalt from sticking
- No soil contamination from diesel
- Biodegradable
- Heat resistant up to 500°F
- Saves time, prevents sticking

CAUTION: Do not take internally. See additional precautionary information on side panel.

KEEP OUT OF REACH OF CHILDREN.NET CONTENTS 55 GAL(S)

CAUTION

Use caution. Contains amino functional silicone compounds. CAS number: N/A – mixture.

FIRST AID

IF IN EYES: Flush with clear cool water for at least 15 minutes. Get medical attention.

IF ON SKIN: Wash with soap and water. If irritation develops, get medical attention.

IF SWALLOWED: Do not induce vomiting. Give plenty of water to dilute stomach contents. Call a physician.

KEEP OUT OF REACH OF CHILDREN.



Reorder C393 800-548-2080



SOLD EXCLUSIVELY BY:





Murrysville Business Park Export. PA 15632 101 Technology Lane (724) 327-7200