

MATERIAL SAFETY DATA SHEET

This MSDS complies with OSHA's Hazard Communication Standard CFR 1910.1200 and OSHA Form 174.

N/A SIGNIFIES NON-APPLICABLE

IDENTITY AND SUPPLIERS INFORMATION

PRODUCT NAME:	DUAL SPACE SPRAY	CHEMICAL FAMILY:		<table><tr><th>HMIS HAZARDOUS MATERIALS IDENTIFICATION SYSTEM</th><th>RATING</th></tr><tr><td>HEALTH</td><td>2</td></tr><tr><td>FLAMMABILITY</td><td>2</td></tr><tr><td>REACTIVITY</td><td>0</td></tr><tr><td>MAX PERSONAL PROTECTION</td><td>B</td></tr></table>	HMIS HAZARDOUS MATERIALS IDENTIFICATION SYSTEM	RATING	HEALTH	2	FLAMMABILITY	2	REACTIVITY	0	MAX PERSONAL PROTECTION	B
HMIS HAZARDOUS MATERIALS IDENTIFICATION SYSTEM	RATING													
HEALTH	2													
FLAMMABILITY	2													
REACTIVITY	0													
MAX PERSONAL PROTECTION	B													
PRODUCT NUMBER:	C400	FORMULA:	PROPRIETARY											
SUPPLIER'S NAME:	GENERAL PRODUCTS & SUPPLY, INC.	PHONE NUMBER:	(724) 327-7200											
SUPPLIER'S ADDRESS:	101 TECHNOLOGY LANE	EMERGENCY NO.:	800-255-3924											
	EXPORT, PA 15632													
PROPER SHIPPING NAME:	COMBUSTIBLE MATERIAL													

SECTION 1 - INGREDIENT IDENTIFICATION AND INFORMATION

CHEMICAL NAME	CARC.	CAS NO.	WT %	SARA III	PEL	TWA-TLV	STEL-TLV
Stoddard solvent type petroleum distillate	d	64742-88-7	> 98		500	100	

SECTION 2 - PHYSICAL/CHEMICAL PROPERTIES

BOILING POINT:	est. 220°F
VAPOR PRESSURE: (mm Hg)	N/D
VAPOR DENSITY:	> 1
SOLUBILITY IN WATER:	Negligible
SPECIFIC GRAVITY:	0.77 - 0.79
pH RANGE:	N/E
EVAPORATION RATE: (Water=1)	> 1
PHYSICAL DESCRIPTION:	Clear, pale yellow fluid with a solvent odor.

SECTION 3 - FIRE/EXPLOSION HAZARD DATA

FLAMMABILITY: (FLAME PROJECTION)	AUTO IGNITION TEMP: N/E
FLASH POINT:	114°F (TCC)
FLAMMABILITY LIMITS:	%UEL 6.0 %LEL 1.0
EXTINGUISHER MEDIA:	Water spray or fog, foam, dry chemical or CO2. Do not use direct waterstream.
SPECIAL FIRE FIGHTING PROCEDURES:	Do not enter confined fire space without proper protective equipment including a NIOSH approved, self-contained breathing apparatus. Cool fire exposed containers, surrounding equipment and structures with water.
UNUSUAL FIRE/EXP. HAZARDS:	None known

SECTION 4 - REACTIVITY HAZARD DATA

STABILITY:	Stable	HAZARDOUS POLYMERIZATION:	Will not occur
INCOMPATIBILITY:	Oxidizing materials		
CONDITIONS TO AVOID:	Heat, sparks and open flame.		
HAZARDOUS DECOMPOSITION PRODUCTS:	Oxides of carbon and unidentified organics may be formed during combustion.		

SECTION 5 - HEALTH HAZARD DATA AND FIRST AID

PRIMARY ROUTES OF ENTRY:	Skin	FIRST AID PROCEDURES:	
ACUTE EFFECTS:	Toxicity: CNS depression producing headache, dizziness, nausea and loss of consciousness.		
SKIN:	Prolonged and repeated liquid contact may result in irritation and dermatitis.	SKIN:	Wash with soap and water. If persistent irritation occurs, get medical attention.
EYES:	Slight irritation from short-term contact. Prolonged and repeated contact more irritating.	EYES:	Flush with water. If persistent irritation occurs, get medical attention.
INHALATION:	High concentrations or prolonged exposure to lower concentrations may be slightly irritating to mucous membranes.	INHALATION:	Remove to fresh air. Provide oxygen if breathing is difficult. Get medical attention.
INGESTION:	May result in vomiting. Aspiration of vomitus into lungs must be avoided as lung contact can result in chemical pneumonitis and pulmonary edema.	INGESTION:	Do not induce vomiting. If vomiting occurs, keep head below hips to prevent aspiration of liquid into lungs. Get medical attention.

SECTION 6 - CONTROL AND PROTECTIVE MEASURES

RESPIRATORY PROTECTION:	As required to prevent overexposure. NIOSH-approved air purifying respirator for organic vapors or atmosphere-supplying respirator.
PROTECTIVE GLOVES:	As required to minimize skin contact
VENTILATION REQUIREMENTS:	Explosion proof ventilation as required to control vapor concentrations
OTHER PROTECTIVE CLOTHING:	Clothing, as required, to minimize skin contact. Eyewash station and safety shower.
HYGIENIC WORK PRACTICE:	Wash hands after handling.

SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IF MATERIAL IS SPILLED OR RELEASED:	Contain spill. Keep out of surface waters and any sewers or water courses entering or leading to surface waters. Soak up with inert absorbent and place in properly labeled, leak-proof containers for disposal.
WASTE DISPOSAL METHODS:	Dispose of in a facility approved for hazardous waste in compliance with all applicable local, state and federal laws, rules and regulations.
PRECAUTIONS IN STORAGE AND HANDLING:	Store in original shipping containers away from heat, open flames and oxidizing materials. Keep closed when not in use. Shelf life is one year.
OTHER PRECAUTIONS:	Keep out of reach of children.

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without any warranty or guarantee of any kind.