

MATERIAL SAFETY DATA SHEET

This MSDS complies with OSHA's Hazard Communication Standard CFR 1910.1200 and OSHA Form 174.

N/A SIGNIFIES NON-APPLICABLE

IDENTITY AND SUPPLIERS INFORMATION						
PRODUCT NAME:	LIQUID DETAILER	CHEMICAL FAMILY:				
PRODUCT NUMBER:	C716	FORMULA:	PROPRIETARY	NFPA HAZARDOUS MATERIALS IDENTIFICATION SYSTEM	RATING	
SUPPLIER'S NAME:	GENERAL PRODUCTS & SUPPLY, INC.	PHONE NUMBER:	(724) 327-7200	HEALTH	1	
SUPPLIER'S ADDRESS:	101 TECHNOLOGY LANE	EMERGENCY NO .:		FLAMMABILITY	2	
	EXPORT, PA 15632			REACTIVITY	0	
PROPER SHIPPING NAME:				MAX PERSONAL PROTECTION	В	

SECTION 1 – INGREDIENT IDENTIFICATION AND INFORMATION							
CHEMICAL NAME	CARC.	CAS NO.	WT %	SARA III	PEL	TWA-TLV	STEL-TLV
MINERAL SPIRITS		8052-41-3			100	525	

SECTION 2 - PHYSICAL/CH	EMICAL PROPERTIES	SECTION 3 - FIRE/EXPLOSION	N HAZARD DATA		
BOILING POINT: VAPOR PRESSURE: (mm Hg @ 70ºF)	310°F 3.0	FLAMMABILITY: (FLAME PROJECTION) FLASH POINT: 110°F	AUTO IGNITION TEMP: N/A		
VAPOR DENSITY:	4.85	FLAMMABILITY LIMITS:	%UEL 7 %LEL 1		
SOLUBILITY IN WATER:	ZERO AT 20°C	EXTINGUISHER MEDIA: Water fog, dry ch	nemical, foam or carbon dioxide.		
SPECIFIC GRAVITY:	0.77	Closed containe	rs exposed to fire may be cooled with		
pH RANGE:	N/A	water.			
EVAPORATION RATE: (BuAc=1)	0.2				
PHYSICAL DESCRIPTION: Clear blue liquid with no odor.		SPECIAL FIRE FIGHTING PROCEDURES:			
		Do not use water except as fog.			
		UNUSUAL FIRE/EXP. HAZARDS:			
		Avoid all ignition sources such as flames and sparks.			

SECTION 4 - REACTIVITY HAZARD DATA

 STABILITY:
 Stable
 HAZARDOUS POLYMERIZATION:
 Will not occur

 INCOMPATIBILITY:
 None known
 Strong oxidizers such as hydrogen peroxide, bromine, and chromic acid.

 CONDITIONS TO AVOID:
 Strong oxidizers such as hydrogen peroxide, bromine, and chromic acid.

 HAZARDOUS DECOMPOSITION PRODUCTS:
 Carbon monoxide and carbon dioxide from burning.

SECTION 5 - HEALTH HAZARD DATA AND FIRST AID

PRIMARY ROUTE ACUTE EFFECTS:	S OF ENTRY: Inhalation, eyes, skin and ingestion	I	FIRST AID PROCEDURES:
SKIN:	Dermatitis.	SKIN:	Remove excess with cloth or paper. Wash thoroughly with soap and water.
EYES: INHALATION: INGESTION:	Irritation. Irritation of eyes, nose and throat, dizziness. Will cause stomach distress, nausea, vomiting. Large amounts, if retained, lead to symptoms of central nervous system depression.	EYES: INHALATION: INGESTION:	Rinse with cool water for 15 minutes and call a physician. Remove to fresh air. Call a physician immediately. Do not induce vomiting. Vomiting may cause aspiration into lungs resulting in chemical pneumonia.

SECTION 6 - CONTROL AND PROTECTIVE MEASURES

RESPIRATORY PROTECTION:

PROTECTIVE GLOVES: VENTILATION REQUIREMENTS: OTHER PROTECTIVE CLOTHING: HYGIENIC WORK PRACTICES: US Bureau of Mines Respirator, self-contained breathing device, airline or NIOSH approved respirator if vapor concentration exceeds permissible exposure limits. Neoprene. EYE PROTECTION: Goggles. Local exhaust None. Keep off of clothing.

SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IF MATERIAL IS SPILLED OR RELEASED: Large spills: Dike and contain for intended use. Small spills: Absorb on an inert ingredient, such as earth. sands or vermiculate.

WASTE DISPOSAL METHODS: PRECAUTION IN STORAGE AND HANDLING: Follow all Local, State, and Federal regulations in your area. Avoid all ignition sources such as flames and sparks. Do not handle or store at temperatures over 38°C (100°F). None.

OTHER PRECAUTIONS:

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without any warranty or guarantee of any kind.