

WATER GUARD is a ready-to-use water borne blend of siloxane and silane designed to provide protection from water intrusion on concrete, block, pavers, flagstone, terra cotta, sandstone and brick. **WATERGUARD** is an excellent means for protecting masonry from the accumulation of water penetration leading to freeze/thaw damage, protection against salt damage, efflorescence, and dirt accumulation. Protection of this nature allows for a lengthening of substrate life.

WATER GUARD is formulated to penetrate deeply into the surface, bond physically and chemically to the substrate to provide extended service life. **WATER GUARD** will remain breathable, is VOC Compliant, and also provides protection against mold and mildew. Do not use this product on limestone, polished surfaces such as marble or granite. **WATER GUARD** should be applied when the temperature is at least 65°F or higher.

DIRECTIONS

Masonry should be thoroughly dry before **WATER GUARD** is applied. Treatment should not be started if temperature is below freezing as the possibility of entrapped water exists. A spray application is preferred but brush on applications can be just as successful.

For spraying use a coarse low pressure spray pattern and thoroughly wet surface. Hold nozzle 6 inches from surface and move nozzle so the solution runs down about 6 to 10 inches from the point of application.

CAS Numbers: Contains Dimethyl, phenyl siloxane, methoxy terminated (68657-04-0) and N-Octyltriethoxysilane (2943-75-1).



C845

GENERAL MAINTENANCE PRODUCTS

WATER GUARD

Silicone Water Repellent

- Waterproofs
- Weatherproofs
- Invisible
- Economical

CAUTION: Combustible material. Contains mineral spirits. Keep away from sparks and open flames.

KEEP OUT OF REACH OF CHILDREN.

NET CONTENTS: 5 GAL(S)

CAUTION

Prolonged or repeated exposure or breathing very high concentrations may cause headaches, nausea, vomiting, and dizziness. Swallowing lesser quantities can cause dizziness, headaches, or nausea. Large amounts, if retained, can lead to symptoms of central nervous system depression. Prolonged or repeated contact may irritate skin causing dermatitis. Vapors will irritate the eyes.

FIRST AID

IF IN EYES: Rinse eyes with cool water for 15 minutes, lifting the upper and lower eyelids occasionally. Immediately obtain medical attention.

IF ON SKIN: Wipe away excess material. Use a waterless hand cleaner to remove as much of material as possible. Wash with soap and water. Remove contaminated clothing and shoes; wash before reuse. Get medical attention if irritation persists after washing.

IF INHALED: Remove to fresh air. Give artificial respiration if not breathing. If breathing is difficult, administer oxygen. If irritation persists, obtain medical advice.

IF SWALLOWED: If conscious, immediately have victim rinse mouth with water. Give victim 2 glasses of water. **DO NOT INDUCE VOMITING.** If vomiting occurs have victim lean forward to reduce the risk of aspiration. Give fluids until the vomitus is clear. Get immediate medical attention. Consider poisoning of methanol. Do not give anything to an unconscious or convulsing person.

KEEP OUT OF REACH OF CHILDREN



Reorder C845
800-548-2080

HMIS RATING	
3 - HEALTH	
2 - FLAMMABILITY	
1 - REACTIVITY	
J - PROTECTIVE EQUIPMENT	

SOLE EXCLUSIVE BY:


General Products & Supply Inc.


GMP
Chemical Solutions

Murrysville Business Park
Export, PA 15632

101 Technology Lane
(724) 327-7200