

R/BE GRAY NON-SKID SAFETY SEALER is a rubber based, pigmented enamel containing coarse silica grit. For interior and exterior use on wood, concrete or steel surfaces that require safe footing. This is a one part system for old or new concrete. Authorized by the USDA, low VOC.

DIRECTIONS

Surface must be dry and free from dirt, rust, grease, oil, and loose paint. For best results, smooth concrete surfaces should be etched with **GMP CONCRETE ETCH**. A stiff brush or trowel is recommended for applying **R/BE GRAY NON-SKID SAFETY SEALER**. No primer or thinner is necessary.

Coverage: single coat application is approximately 50 sq. ft. per gallon when applied within 24 hours of first application. This will also produce the best adhesion.

CAS Numbers: Contains titanium dioxide (13463-67-7), aluminum hydroxide (21645-51-2), amorphous silica (7631-86-9), p.m. acetate benzenes (1551-13-7), carbon black (1333-86-4), chlorinated paraffin (61788-76-9), xylene (1330-20-7), and mineral spirits (64741-92-0).

The balance of the chemicals in this mixture are either considered non-hazardous or are below the listing limits (1% for hazardous substances, 0.01% for special hazardous substances) under various State Right-To-Know laws. These chemicals are considered trade secrets. The specific chemical identity of these chemicals is available to health professionals. This product contains one or more materials subject to the reporting requirements of section 313 of the Emergency Planning and the Community Right-To-Know Acts of 1986 and of 40 CFR 372.

WARNING

Use only with adequate ventilation. Do not breathe vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness, or if air monitoring demonstrates vapor/mist levels above applicable limits, wear an appropriate, properly fitted respirator. Close container after each use. Avoid contact with eyes, skin, and clothing. Wash thoroughly after handling.

GMP
Chemical Solutions

C849

GENERAL MAINTENANCE PRODUCTS

R/BE GRAY NON-SKID SAFETY SEALER Rubber-based Enamel Concrete Sealer

- Permanent, non-slip surface
- For interior or exterior use
- RTU—no primer or thinner necessary
- Designed for use on wood, steel, or concrete
- Worker safe, low VOC
- One part system

CAUTION: Keep all perishable food out of area. See side panel for additional precautionary information.

KEEP OUT OF REACH OF CHILDREN.
NET CONTENTS 5 GAL(S)

(**WARNING, cont.**) Combustible liquid. Vapor harmful or fatal if swallowed. May affect the brain or nervous system causing dizziness, headache, or nausea. Causes eye, skin, nose, and throat irritation. Keep away from heat and flame. Prevent buildup of vapors by opening all windows and doors to achieve cross ventilation.

NOTE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

FIRST AID

IF IN EYES: Flush with large amounts of cool water for at least 15 minutes. Consult a physician.

IF ON SKIN: Wash thoroughly with soap and water. If irritation persists, consult a physician.

IF INHALED: Remove to fresh air, administer oxygen if available, to restore breathing. If spontaneous vomiting occurs, take steps to prevent aspiration into the lungs. If irritation persists, consult a physician.

IF SWALLOWED: Contact nearest Poison Control Center. Do not induce vomiting.

KEEP OUT OF REACH OF CHILDREN.

Reorder C849
800-548-2080

HMS RATING

2 - FLAMMABILITY

2 - HEALTH

0 - REACTIVITY

G - PERSONAL PROPERTY

SOLD EXCLUSIVELY BY:


General Products & Supply Inc.

Murrysville Business Park
Export, PA 15632

GMP
Chemical Solutions

101 Technology Lane
(724) 327-7200