

GLEAM DURASEAL is a clear, non-yellowing, high solids, low odor, interior/exterior masonry sealer. Use on previously coated or uncoated, vertical or horizontal surfaces including concrete, pavers, Mexican tile, unglazed tile, brick, aggregate, masonry and stucco. NOTE: This product is not recommended for wood, metal, granite, marble, terrazzo, areas adjacent to pools or around areas subject to hydrostatic pressure. Do not use over oil-based products.

DIRECTIONS:

Surface preparation: All surfaces should be clean and free of dirt and greasy soils. See your **GMP** Representative for recommendations for proper cleaning agents for your specific substrate and soil condition. New concrete should cure for at least 30 days prior to sealing. New, smooth concrete surfaces should be cleaned with **GMP SANSELY GREEN** and etched, if necessary, with **GMP CONCRETE ETCH** before using **GLEAM DURASEAL**.

Application: Do not thin. Use when temperatures are between 50-80 degrees F. Do not apply in direct sunlight. Do not apply to wet surfaces or if rain is expected within 24 hours. Apply thin coat using a 1/4" - 3/8" nap roller, a PADCO applicator, or airless sprayer. Spread rate is highly dependent on surface roughness and porosity. Spreads at 500 to 1,000 sq. ft. per gallon. If sprayed, backroll for uniform thickness. Allow first coat to dry for four hours, then apply a second coat. Additional coats should be added for a higher gloss and added protection. Dries to touch in one hour. Longer dry time required in cooler temperatures and also in higher humidity environments. Floors may be subject to light foot traffic after 24 hours. Allow 72 hours before repositioning furniture or subjecting surface to heavy traffic. Park tires on corrugated cardboard for 14 days after applying product.

GMP
Chemical Solutions

C873

GENERAL MAINTENANCE PRODUCTS

GLEAM DURASEAL
Interior/Exterior Seal

- Seals, Protects & Beautifies Concrete & Masonry Surfaces
- High Gloss, Wet Look Finish
- Forms a Hard Protective Film
- Resists Hot Tire Pick-up
- Increases Surface Life
- Reduces Maintenance Time

CAUTION: Do not take internally. See side panel for additional precautionary information.

KEEP OUT OF REACH OF CHILDREN

NET CONTENTS: 1 GAL(S)

CAUTION

Use caution. Do not store in areas where product may freeze.

FIRST AID

IF IN EYES: Flush eyes with large quantities of clear, cool water. Seek medical attention if irritation persists.

IF ON SKIN: Remove contaminated clothing. Flush affected areas with water. Prolonged contact may cause dermatitis. Seek medical attention if irritation persists.

IF SWALLOWED: Drink a large quantity of water. Seek medical attention immediately.

CAS NUMBERS: Contains Water (7732-18-5), Acrylic Copolymers mixture N/A, Propylene Glycol Phenyl Ether (000770-35-4).



Reorder C873
800-548-2080

HMIS RATING	
1 - HEALTH	
0 - FLAMMABILITY	
0 - REACTIVITY	
A - PROTECTIVE EQUIPMENT	

SOLD EXCLUSIVELY BY:


General Products & Supply Inc.

Murrysville Business Park
Export, PA 15632

GMP
Chemical Solutions

101 Technology Lane
(724) 327-7200

