

MATERIAL SAFETY DATA SHEET

This MSDS complies with OSHA's Hazard Communication Standard CFR 1910.1200 and OSHA Form 174.

N/A SIGNIFIES NON-APPLICABLE

IDENTITY AND SUPPLIERS INFORMATION

PRODUCT NAME:	IMPERIAL GYM FINISH	CHEMICAL FAMILY:		<table><tr><th>HMIS HAZARDOUS MATERIALS IDENTIFICATION SYSTEM</th><th>RATING</th></tr><tr><td>HEALTH</td><td>2</td></tr><tr><td>FLAMMABILITY</td><td>2</td></tr><tr><td>REACTIVITY</td><td>0</td></tr><tr><td>MAX PERSONAL PROTECTION</td><td>B</td></tr></table>		HMIS HAZARDOUS MATERIALS IDENTIFICATION SYSTEM	RATING	HEALTH	2	FLAMMABILITY	2	REACTIVITY	0	MAX PERSONAL PROTECTION	B
HMIS HAZARDOUS MATERIALS IDENTIFICATION SYSTEM	RATING														
HEALTH	2														
FLAMMABILITY	2														
REACTIVITY	0														
MAX PERSONAL PROTECTION	B														
PRODUCT NUMBER:	C890	FORMULA:	PROPRIETARY												
SUPPLIER'S NAME:	GENERAL PRODUCTS & SUPPLY, INC.	PHONE NUMBER:	(724) 327-7200												
SUPPLIER'S ADDRESS:	101 TECHNOLOGY LANE EXPORT, PA 15632	EMERGENCY NO.:	800-255-3924												
PROPER SHIPPING NAME:	COMBUSTIBLE MATERIAL														

SECTION 1 - INGREDIENT IDENTIFICATION AND INFORMATION

CHEMICAL NAME	CARC.	CAS NO.	WT %	SARA III	PEL	TWA-TLV	STEL-TLV
Solvent naptha (petroleum), medium aliphatic	d	64742-88-7	> 50		500 ppm	100 ppm	

SECTION 2 - PHYSICAL/CHEMICAL PROPERTIES

SECTION 3 - FIRE/EXPLOSION HAZARD DATA

BOILING POINT:	> 300°F	FLAMMABILITY: (FLAME PROJECTION)	AUTO IGNITION TEMP: N/E
VAPOR PRESSURE: (mm Hg @ 100°F)	< 5	FLASH POINT:	111°F (TCC)
VAPOR DENSITY:	5.0	FLAMMABILITY LIMITS:	%UEL 6.0 %LEL 1.0
SOLUBILITY IN WATER:	Negligible	EXTINGUISHER MEDIA:	Water fog, foam, dry chemical or CO2. Do not use direct water stream.
SPECIFIC GRAVITY:	0.82 - 0.88	SPECIAL FIRE FIGHTING PROCEDURES:	
pH RANGE:	N/D	Use proper protective equipment including a NIOSH approved, self-contained breathing apparatus. Cool fire-exposed containers, surrounding equipment and structures with water.	
EVAPORATION RATE: (BuAc =1)	0.07	UNUSUAL FIRE/EXP. HAZARDS:	
PHYSICAL DESCRIPTION:	Clear to slightly hazy, light amber liquid with hydrocarbon odor.	Burning product will float on water, possibly spreading fire to new locations.	

SECTION 4 - REACTIVITY HAZARD DATA

STABILITY:	Stable	HAZARDOUS POLYMERIZATION:	Will not occur
INCOMPATIBILITY:	Oxidizing materials		
CONDITIONS TO AVOID:	Heat, sparks and open flames		
HAZARDOUS DECOMPOSITION PRODUCTS:	Oxides of carbon, unidentified organics and traces of cobalt, zinc and lead compounds.		

SECTION 5 - HEALTH HAZARD DATA AND FIRST AID

ACUTE EFFECTS: Toxicity: Overexposure can lead to CNS depression producing headaches, dizziness, nausea and loss of consciousness.

SKIN:	Prolonged or repeated contact can cause defatting resulting in irritation and dermatitis.	FIRST AID PROCEDURES:	
EYES:	Liquid or vapor contact may result in eye irritation.	SKIN:	Remove contaminated clothing. Wash with soap and water. If persistent irritation occurs, get medical attention.
INHALATION:	High concentrations or prolonged exposures to lower concentrations may be slightly irritating to mucous membranes. Aspiration of liquid may cause chemical pneumonitis.	EYES:	Flush with water. If persistent irritation occurs, get medical attention.
INGESTION:	May result in vomiting. Aspiration of vomitus must be avoided. (See inhalation above.)	INHALATION:	Remove to fresh air. Provide oxygen or artificial respiration as needed. Get medical attention.
		INGESTION:	Do not induce vomiting. If vomiting occurs, keep head below hips to prevent aspiration of liquid into lungs. Get medical attention.

SECTION 6 - CONTROL AND PROTECTIVE MEASURES

RESPIRATORY PROTECTION:	None generally needed under normal handling and usage conditions.	EYE PROTECTION:	Safety glasses or chemical goggles
PROTECTIVE GLOVES:	Solvent resistant		
VENTILATION REQUIREMENTS:	If natural ventilation is not adequate to maintain concentrations below 100 ppm, use explosion-proof ventilation.		
OTHER PROTECTIVE CLOTHING:	Eyewash station and safety shower		
HYGIENIC WORK PRACTICE:	Do not eat, drink or smoke in work area. Wash hands after handling.		

SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IF MATERIAL IS SPILLED OR RELEASED:	Contain spill. Do not contaminate sewers, surface or ground waters. Soak up spill in inert absorbent material. Place in non-leaking containers. Seal containers and label them properly for legal disposal.
WASTE DISPOSAL METHODS:	Consult with appropriate federal, state and local authorities to determine method of disposal in compliance with federal, state and local regulations.
PRECAUTIONS IN STORAGE AND HANDLING:	Store in original shipping containers. Store away from heat, sparks, open flame and oxidizing materials. Keep closed when not in use. Shelf life is one year.
OTHER PRECAUTIONS:	Do not cut, weld or drill on or near full, part-full or empty drums. Keep out of reach of children.
We believe the statements, technical information and recommendations contained herein are reliable, but they are given without any warranty or guarantee of any kind.	