

DRY-KLEEN is designed for use on wood floor and surfaces where water would harm the surfaces. It will remove dirt and spills without harming the surface. It can also be used to remove rubber burns, black heel marks and other hard to remove items from the surface without the use of water.

DIRECTIONS FOR USE

STIR WELL BEFORE USING.

APPLICATION TEMPERATURE: 50°F to 90°F.

AS A CLEANER ONLY ON SEALED FLOORS: Damp mop floor with waterless cleaner. Use the heel of the mop on stubborn spots and damp rinse the floor with a clean mop and **DRY-KLEEN**.

PREPARING SEALED FLOORS FOR RECOATING: Clean away water soluble soil (food or sugar) by damp mopping or wet scrubbing and allow to dry. Care must be taken not to warp the floor by allowing water to penetrate into the wood. To abrade the floor for good intercoat adhesion, and to remove black marks, etc., mop **DRY-KLEEN** onto floor 3 to 4 minutes ahead of a black wax stripping pad under a rotary machine. Move machine at the pace of a slow walk in full head passes, overlapping 1 to 2 inches. Tack rag with **DRY-KLEEN** to remove dust residue. Use the single pass applicator to continuously feed solvent to the tack rag. This will greatly increase the efficiency of the tack rag process.

NEWLY SANDED OR FULLY STRIPPED FLOORS: If chemically stripped, scrub with waterless cleaner to remove stripper residue and pick up soiled solution with wet vacuum or mop. Rubber burns, black marks, etc., may be removed with a cloth dampened with **DRY-KLEEN**. **DRY-KLEEN** will soften gum so that it may be removed with a putty knife.

DRYING TIME: @70°F

CLEAN-UP: Use mineral spirits.

SHELF LIFE: 1 year from date of invoice in original, unopened container.

GMP
Chemical Solutions

C897

GENERAL MAINTENANCE PRODUCTS

DRY-KLEEN

Wood and Gym Cleaner

- Leaves No Residue
- Colorless
- Removes Oil, Grease, & Black Marks Without The Use Of Water
- Cleans All Sealed Wood
- Will Not Swell Or Buckle Wood
- 350 to 500 Square Feet Per Gallon

DANGER: May be fatal if swallowed and enters airways. Combustible liquid.

KEEP OUT OF REACH OF CHILDREN

NET CONTENTS: 1GAL(S)

DANGER



COMBUSTIBLE. Keep out of reach of children. Keep away from heat and open flame, contains flammable thinners. Use with adequate ventilation. Avoid smoking when applying. Do not store in hot areas. Harmful or fatal if swallowed. Avoid breathing of vapor or spray mist and prolonged contact with skin. Do not take internally. Wash hands thoroughly after handling and before eating or smoking. Keep container closed while not in use.

If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

READ MSDS COMPLETELY BEFORE USING THIS PRODUCT.

FIRST AID

IF IN EYES: Flush immediately with plenty of water for at least 15 minutes and get medical attention immediately.

IF YOU EXPERIENCE DIFFICULTY IN BREATHING: Leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately.

IF SWALLOWED: DO NOT INDUCE VOMITING. Get medical attention immediately.

EXTERNAL: Wash hands thoroughly after handling.

CAS Numbers: Contains Hydrocarbon Solvent (64742-88-7) and Aromatic Hydrocarbon (64742-95-6).

KEEP OUT OF REACH OF CHILDREN



Reorder A787
800-548-2080

SOLD EXCLUSIVELY BY:

General Products & Supply Inc.

Murrysville Business Park
Export, PA 15632

HMIS RATING
2 - HEALTH
2 - FLAMMABILITY
0 - REACTIVITY
B - PROTECTIVE EQUIPMENT

GMP
Chemical Solutions

101 Technology Lane
(800) 548-2080