

MATERIAL SAFETY DATA SHEET

This MSDS complies with OSHA's Hazard Communication Standard CFR 1910.1200 and OSHA Form 174.

NGINEERED

AINTENANCE

N/A SIGNIFIES NON-APPLICABLE									
IDENTITY AND SU	JPPLIERS INFORMATIC	ON							
PRODUCT NAME:	MULTIPLEX EP GREASE	CHEI	MICAL I	FAMILY:					
GMP PRODUCT NUMBER: LU100		FORMULA:		PROPRIETARY		HMIS HAZARDOUS MATERIALS IDENTIFICATION SYSTEM		S RATING	
SUPPLIER'S NAME:	LY, INC. PHO	, INC. PHONE NUMBER: (724) 327-7200) 327-7200	HEALTH		0		
SUPPLIER'S ADDRESS:		EMERGENCY NO.: 800-255-392			FLAMMABILITY		1		
SUPPLIER'S ADDRESS: 101 TECHNOLOGY LANE EXPORT, PA 15632		DATE PREPARED		ARED:		REACTIVITY	REACTIVITY		
PROPER SHIPPING NAME					MAX PERSONAL PROTECTION		0		
SECTION 1 - INGR	REDIENT IDENTIFICATI	ON AND INFO	RMA	TION				I	
CHEMICAL NAME		CARC.	. CAS NO.		WT.%	PEL	TWA-TLV		
Solvent refined heavy par		64741-88-4		30-40					
Hydrotreated heavy naph Hydrotreated residual oils		64742-52-5 64742-57-0		30-40 10-15					
Antimony dialkylidithioca		15890-25-2			0-2				
Zinc oxide		1314-13-2			0-3				
SECTION 2 - PHYSICAL/CHEMICAL PROPERTIES				SECTIO	SECTION 3 - FIRE/EXPLOSION HAZARD DATA				
BOILING POINT: VAPOR PRESSURE: (Non VAPOR DENSITY (Air = 1): SOLUBILITY IN WATER: SPECIFIC GRAVITY (H2O pH: EVAPORATION RATE: (W. PHYSICAL DESCRIPTION	ligible)	@ 68⁰F jible , tacky grease, bland,		FLAMMABILITY: AUTO IGNITION TEMP: FLASH POINT (of Concentrate Only): 380°F FLAMMABILITY LIMITS: %UEL N/A %UEL N/A %LEL N/A EXTINGUISHER MEDIA: Foam, dry chemical, CO2, water, fog, or spray. SPECIAL FIRE FIGHTING PROCEDURES: Use air-supplied breathing equipment for enclosed areas. Cool exposed containers with water spray. Avoid breathing vapors or fumes. UNUSUAL FIRE/EXP. HAZARDS: Do not mix or store with strong oxidants like chlorine or concentrated oxygen. Empty product containers retain product residue-do not pressurize, cut, heat, weld or expose such containers to flame. They may explode and cause injury or death.					
SECTION 4 - REA	CTIVITY HAZARD DAT	4							
STABILITY: Stable HAZARDOUS POLYMERIZATION: Will not occur INCOMPATIBILITY: Strong oxidants such as liquid chlorine, concentrated oxygen, sodium or calcium hypochlorite. CONDITIONS TO AVOID: HAZARDOUS DECOMPOSITION PRODUCTS:									
SECTION 5 - HEA	LTH HAZARD DATA AN	ID FIRST AID							
ACUTE EFFECTS:				FIRST AID PROCEDURES:					
Prolonged or repeated liquid contact with skin may cause mild irritation.				(IN: Remove any contaminated clothing. Wash water.			othing. Wash skin w	ith soap and	
	imation.	EYES: Flush with cle INHALATION: 5 mg/m ³ for c		ear water for 15 minutes or until irritation subsides. bil mist in air. ian immediately.					
SECTION 6 - CON	TROL AND PROTECTIV	VE MEASURE	S						
RESPIRATORY PROTECTION: Normally not needed. Use air-supplied respiratory protection in confined or enclosed spaces, if needed. PROTECTIVE GLOVES: Use chemical resistant gloves, if needed, to avoid prolonged skin contact. EYE PROTECTION: Use local exhaust to capture fumes and vapors. Provide greater than 60 fpm or face velocity for confined spaces. HYGIENIC WORK PRACTICES: Do not work in oil soaked clothing. Wash after handling.									
SECTION 7 - PRE	CAUTIONS FOR SAFE								
STEPS TO BE TAKEN IF MA	Open all windo	Open all windows and doors. Keep petroleum products out of sewers and watercourses by diking or impounding. Advise authorities if product has entered, or may enter, sewers, watercourses, or extensive							
WASTE DISPOSAL METHO		Assure conformity with applicable disposal regulations. Dispose of absorbed materials at an approved							
PRECAUTIONS IN HANDLIN	Keep containe	Keep containers closed when not in use. Do not handle or store near heat, sparks, flame, or strong							
OTHER PRECAUTIONS:		oxidants. KEEP OUT OF REACH OF CHILDREN. Empty containers may contain explosive gas.							

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without any warranty or guarantee of any kind.