

MOLY MULTIPLEX is a lithium-complex grease-black in color that contains a full 3% Moly. Due to its high drop point and the large quantity of polymers it is a very versatile grease for multi-purpose extreme pressure applications. The versatility of **MOLY MULTIPLEX** makes this lubricant very cost effective by reducing and eliminating the inventory of several specialty greases. The tackiness of **MOLY MULTIPLEX** makes it highly suitable as an open gear grease especially when a clean grease is preferred. **MOLY MULTIPLEX** is highly recommended for and has been field tested as a truly "heavy duty" industrial grease with multiple applications.

PRECAUTIONS

Misuse of empty containers can be hazardous. Empty containers can be dangerous if used to store toxic, flammable, or reactive materials. Cutting or welding of empty containers might cause fire, explosion, or toxic fumes from residue. Do not pressurize or expose to open flame or heat. Keep container closed and drum bungs in place.

KEEP OUT OF REACH OF CHILDREN.

Do not ingest.

PRODUCT # LU101-35



Engineered
Maintenance
Lubricants

MOLY MULTIPLEX EP GREASE NLGI #2

- High Timken Rating
- Waterproof
- Acid Resistant
- Adhesive and Cohesive
- High Temperature (550°F)
- Shear Stable
- Contains 3% Molybdenum Disulfide (MoS₂)

KEEP OUT OF REACH OF CHILDREN

NET CONTENTS: 35 Lb(s)

MOLY MULTIPLEX can be used for wheel bearings (with disc or conventional brakes), chasis, fifth wheels, roller and ball bearings, water pumps, bucket pins, ball joints, universal joints, and king pins. Meets CAT and MACK specifications for a full 3% Moly Grease.

INGREDIENTS

Severely highly treated heavy Naphthenic distillates (CAS 64742-52-5), solvent refined heavy paraffinic distillates (CAS 64741-88-4), residual oils hydrotreated (CAS 64742-57-0), antimony dialkylthiocarbamate (CAS 15890-25-2), and molybdenum disulfide (CAS 1317-33-5). **WARNING:** Always follow **OEM** Machine Lubrication Instructions for proper lubrication procedures.

FIRST AID

EYES: Flush with large amount of clear water for at least 15 minutes or until irritation subsides.

SKIN: Remove any contaminated clothing and wash skin with soap and warm water.

IF SWALLOWED: Call physician immediately.

GHS: No GHS Pictograms

SIGNAL WORD: None

D.O.T. SHIPPING INFORMATION:

Not Considered DOT hazardous

Reorder LU101
800-548-2080

SOLD EXCLUSIVELY BY:


General Products & Supply Inc.

Murrysville Business Park
Export, PA 15632

HMS RATING

0- HEALTH

1 - FLAMMABILITY

0 - REACTIVITY

- - PROTECTIVE EQUIPMENT

GMP
Chemical Solutions

101 Technology Lane
(800) 548-2080