

OG PLUS 5 is a semi-synthetic grease, black in color. Due to its nonmelt characteristics, it is for use where extremely high temperatures are present and normal greases will not work. **OG PLUS 5** is *not* a bearing lubricant. It is designed specifically for open gears, sliding surfaces, and fifth wheels. Because of its high percentage of solids, it would be detrimental in bearing use.

PRECAUTIONS

Misuse of empty containers can be hazardous. Empty containers can be dangerous if used to store toxic, flammable, or reactive material. Cutting or welding of empty containers might cause fire, explosion, or toxic fumes from residues. Do not pressurize or expose to open flame or heat. Keep container closed and drum bungs in place. **KEEP OUT OF REACH OF CHILDREN.** Do not ingest.

PRODUCT #LU102-35



Engineered
Maintenance
Lubricants

OG PLUS 5 Open Gear Compound

- Waterproof
- Acid resistant
- Adhesive and cohesive
- Non-melt
- Shear/mechanically stable

NET CONTENTS 35 LB(S)

OG PLUS 5 can be used for fifth wheels, drag lines, cables, sliding surfaces, low speed chains, open gears, spur gears, beveled gears, outside worm gears, dryer drums in asphalt plants, foundries, cranes, and shovels.

FIRST AID

IF IN EYES: Flush with large amounts of water for at least 15 minutes or until irritation subsides.

IF ON SKIN: Remove any contaminated clothing and wash skin with soap and water.

IF INGESTED: Call physician immediately.

KEEP OUT OF REACH OF CHILDREN

Reorder LU102
800-548-2080

HMIS RATING
0 - HEALTH
1 - FLAMMABILITY
0 - REACTIVITY
-- PROTECTIVE EQUIPMENT

SOLD EXCLUSIVELY BY:


General Products & Supply Inc.

Murrysville Business Park
Export, PA 15632

GMP
Chemical Solutions

101 Technology Lane
(800) 548-2080