

**TO2 ULTRA TORQUE TRACTOR HYDRAULIC FLUID** is a truly universal tractor transmission hydraulic fluid. It is compounded from the highest VI solvent-refined paraffinic mineral oils plus the latest state-of-the-art technology additives. **TO2 ULTRA TORQUE TRACTOR HYDRAULIC FLUID** provides extreme pressure protection for maximum gear life and capacity for wet brakes, power-take-offs, clutches, wet clutches, and excellent wet brake noise suppressant. **TO2 ULTRA TORQUE TRACTOR HYDRAULIC FLUID** also has excellent filterability characteristics. Typical applications for **TO2 ULTRA TORQUE TRACTOR HYDRAULIC FLUID'S** are farm tractors, fork lifts, hydraulics, hydrostatic drives, front end loaders, differential wet brake/clutches, transmissions, power-take-offs, and construction equipment with common sub-hydraulic systems.

**TO2 ULTRA TORQUE TRACTOR HYDRAULIC FLUID** meets and exceeds the following specifications: John Deere RES 10060 and J20A, Quatrol, J20B, Ford M2C134-D, MC86-C, M2C41-B, M2C53-A, M2C134-A, M2C134-B, M2C86-B; Massey Ferguson M1135, M1141, M1110, M1127, M1129-A; Case/International JIC-145/MS1210, JIC-185/MS-11204; Kubota; White Farm Q-1826, Q-1705, Q-1766, Q-1802; Steiger; Versatile; Landini; and Fiat-Hesston. This product contains petroleum oil (CAS 64742-54-7).

SOLD EXCLUSIVELY BY:

  
General Products & Supply Inc.

101 Technology Ln.  
Export, PA 15632

Reorder LU600  
800-548-2080



(800) 548-2080  
www.gmpgeneralproducts.com



Engineered  
Maintenance  
Lubricants

## TO2 ULTRA TORQUE TRACTOR HYDRAULIC FLUID

- High VI Base Oils
- Demulsible
- Proprietary Additives
- EP Additives

KEEP OUT OF REACH OF CHILDREN  
NET CONTENTS: 5 GAL(S)

GHS



SIGNAL WORD: **WARNING**

### HAZARD STATEMENTS

H315 - Causes skin irritation  
H320 - Causes eye irritation  
H412 - Harmful to aquatic life with long lasting effects

### PRECAUTIONARY STATEMENTS

P273 - Avoid release to the environment.  
P302+352 - IF ON SKIN: Wash with soap and water.  
P305+351+338 - IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.

### D.O.T. SHIPPING INFORMATION

Not Considered DOT hazardous

### FIRST AID

Eye Contact: Flush with water for several minutes. If effects occur, consult a physician.  
Skin Contact: Wash with soap and water. Remove contaminated clothing and wash before reuse. Get medical attention if needed.  
Inhalation: If symptoms develop, move victim to fresh air. If symptoms persist, obtain medical attention.  
Ingestion: Rinse mouth with water. If symptoms develop, obtain medical attention.

### HANDLING PRECAUTIONS

Avoid contact with eyes, skin, or clothing.  
Keep away from sources of ignition.  
Handle with care and avoid spillage on the floor (slippage).  
Do not cut, weld, drill, grind, braze, or solder container.

BATCH NUMBER: 160400692