

www.gmpgeneralproducts.com

## #LU600 TO2 Ultra Torque - Tractor Hydraulic Fluid

# Tech Bulletin

Proa			

TO2 Ultra Torque TH Fluid provides excellent extreme pressure protection for maximum gear life and capacity for wet brakes and power-take-off clutches, excellent wet brake noise suppression and filterability characteristics.

TO2 Ultra Torque TH Fluid is able to achieve these results while meeting requirements for corrosion and rust inhibition, water tolerance, and temperature operation range. This data is supported in the form of approvals from major manufacturers and extensive field service trial experience.

#### Suitable for Use

TO2 Ultra Torque TH Fluid is suitable for use in applications specifying the following fluids:

Massey-Ferguson CMS M1145	JCMAS HK P-041
Massey-Ferguson CMS M1143	JCMAS HKP-042
Massey-Ferguson CMS M1141	John Deere J-20C
Massey-Ferguson CMS M1138	Komatsu
Massey-Ferguson CMS M1135	Kubota UDT

Permatran III Parker Dennison UTTO, HF-0-HF-02
White Q-1826 Volvo VCE 1273.03
Allison C-4 Volvo WB101

API GL-4 Danfoss HydroStatic Trans Fluid

Case NewHolland MAT3505 Steiger HydrTrans Fluid
Case NewHolland MAT3525 Sauer Sunstrand

Case NewHolland MAT3526 Sperry Vickers/Eaton I-286S ESN M2C86B Sperry Vickers/Eaton M2950S Eaton Vickers 694 ATS-373 w/35VQ25 HyTran Plus and HyTran Ultra

JI Case MS-1204 through MS 1206 B-6 by

HyTran JI Case MS-1210

#### Typical Properties

### <u>Property</u> <u>TO2 Ultra Torque</u>

Gravity, °API	31.1
Flash Point, COC, Deg F (C)	> 350(177)
Pour Point, DegF (C)	-30 (-34)
Viscosity at 40 Deg C, cSt	42
Viscosity at 100 Deg C, cSt	9.2
Viscosity Index	162
Copper Corrosion Test	Pass
Foam Test	Pass
Sulfated Ash, Weight %	< 2.0
Color	< 5

A Division of:

General Products & Supply Inc.

MURRYSVILLE BUSINESS PARK ● 101 TECHNOLOGY LANE ● EXPORT, PA 15632 ● (800) 548-2080 ● FAX (724) 325-4522