

PENELUBE / M.D. contains no silicones or chlorinated solvents which affect plastics, lacquers, insulation, and paint. **PENELUBE / M.D.** Provides rapid displacement and separation of water, and leaves an excellent film protection.

A jet-spray from a pressurized sprayer aids in rapid penetration through mine dust to lubricate Wire, Cable, Rope, and Chain. **PENELUBE / M.D.** also penetrate through rust and corrosion to free frozen parts. Leaves a long lasting lubricating film which defends against water and future corrosion. Provides effective lubrication over a broad range of temperatures and pressures.

DIRECTIONS: Saturate part to be loosened and allow product to penetrate for a moment before attempting to break free. For heavily encrusted pieces a wire brush may be used to help remove corrosion. Apply a light final spray to all parts prior to reassembly.

CAS NO: Naphtha, Petroleum, Heavy Alkylate (64741-65-7) Calcium Sulfonate (Proprietary) Calcium

SOLD EXCLUSIVELY BY:


General Products & Supply Inc.

101 Technology Ln.
Export, PA 15632

Reorder LU605
800-548-2080



(800) 548-2080
www.gmpgeneralproducts.com



Engineered
Maintenance
Lubricants

PENELUBE / M.D.

MINE DUST PENETRANT LUBRICANT

- Penetrates & Lubricates Wire, Cable, Rope & Chains
- Loosens Nuts & Bolts
- Frees Encrusted Parts
- Prevents Corrosion
- Leaves Film Protection

DANGER:
See side panel for precautionary information.
KEEP OUT OF REACH OF CHILDREN
NET CONTENTS: 5 GAL(S)

F
O
R




P
R
O
F
E
S
S
I
O
N
A
L

O
R

I
N
D
U
S
T
R
I
A
L

U
S
E

O
N
L
Y

| GHS | |
|---|----------------------------|
|    | |
| SIGNAL WORD: DANGER | |
| HAZARD STATEMENTS | |
| H226 - Flammable liquid and vapor H315 - Causes skin irritation H336 - May cause drowsiness or dizziness H304 - May be fatal if swallowed and enters airways | |
| PRECAUTIONARY STATEMENTS | |
| P210 - Keep away from heat/sparks/open flames/hot surfaces. No smoking P261 - Avoid breathing dust/fume/gas/mist/vapors/spray. P302+352 - IF ON SKIN: Wash with soap and water. | |
| FIRST AID | |
| Eye Contact: Flush with water for several minutes.If effects occur, consult a physician. Skin Contact: Wash with soap and water. Remove contaminated clothing and wash before reuse.Get medical attention if needed. Inhalation: If symptoms develop, move victim to fresh air.If symptoms persist, obtain medical attention. Ingestion: Rinse mouth with water.If symptoms develop, obtain medical attention. | |
| HANDLING PRECAUTIONS | |
| Avoid contact with eyes, skin, or clothing. Handle with care and avoid spillage on the floor (slippage). Keep away from sources of ignition: Hot surfaces may ignite the product. Vapors are heavier than air, so they may travel across the ground and reach remote ignition sources. Static electricity may accumulate and create a fire hazard. Bond and ground handling equipment and transfer containers to prevent sparking. Do not cut, weld, drill, grind, braze, or solder container. | |
| D.O.T. SHIPPING INFORMATION | |
| NA 1993, Class: -, Proper Shipping Name: Combustible liquid, n.o.s. Technical Shipping Name: Contains Petroleum Naphtha Packing Group: III | |
| UN 1993 | BATCH NUMBER: 160761346 |