

**SURE FLOW** is a concentrated Diesel Fuel Additive specially formulated to control break up wax crystals which form during cold weather operation of diesel engines. Additives enable diesel fuel to flow through filters at very low temperatures. **SURE FLOW** is formulated with flow improvers to prevent low temperature gelling, special anti-gumming dispersants; moisture displacing totally neutralizes the effects of water in fuel, and contains deicing agents. Reduces the pour point of fuel up to 30°F and reduces the cold filter plug point up to 15°F.

**SURE FLOW** minimizes the kerosene usage required for pour point reduction.

Sure Flow Diesel Fuel additive complies with the Federal Ultra Low Sulfur content requirements for use in Diesel Motor Vehicles and Non-road Equipment Engines.

#### **SURE FLOW**

8 ounces (1 Pint)  
16 ounces (1/2 quart)  
32 ounces (1 quart)  
64 ounces (1/2 gallon)  
1 gallon

#### **#2 DIESEL FUEL**

93.75 gallons  
187.50 gallons  
375 gallons  
750 gallons  
1,500 gallons

**DANGER: COMBUSTIBLE LIQUID.  
HARMFUL OR FATAL IF SWALLOWED.  
KEEP OUT OF REACH OF CHILDREN.**

Reorder LUC109  
800-548-2080

SOLD EXCLUSIVELY BY:

  
General Products & Supply Inc.



101 Technology Lane (800) 548-2080  
Export, PA 15632 www.gmpgeneralprocusts.com



Engineered  
Maintenance  
Lubricants

## **SURE FLOW WINTER BLEND ANTI-ICING AGENT**

- Fuel Flow Improver
- Highly Concentrated
- Breaks Up Wax Crystals
- Deicing Agent
- Neutralizes Water in Fuel
- Prevents Fuel Gelling

**KEEP OUT OF REACH OF CHILDREN**

**NET CONTENTS: 55 Gallons**

GHS



**SIGNAL WORD: WARNING**

#### **HAZARD STATEMENTS**

H335 - May cause respiratory irritation  
H336 - May cause drowsiness or dizziness  
H351 - Suspected of causing cancer  
H411 - Toxic to aquatic life with long lasting effects  
H226 - Flammable liquid and vapor

#### **PRECAUTIONARY STATEMENTS**

P210 - Keep away from heat/sparks/open flames/hot surfaces. No smoking  
P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.  
P273 - Avoid release to the environment.  
P240 - Ground/bond container and receiving equipment.

#### **FIRST AID**

Eye Contact: Flush with water for several minutes. If effects occur, consult a physician.  
Skin Contact: Wash with soap and water. Remove contaminated clothing and wash before reuse. Get medical attention if needed.  
Inhalation: If symptoms develop, move victim to fresh air. If symptoms persist, obtain medical attention.  
Ingestion: Rinse mouth with water and drink 2-4 cups of water. Get immediate medical attention. Note to Physician: Activated charcoal may be administered.

#### **HANDLING PRECAUTIONS**

Avoid contact with eyes, skin, or clothing.  
Handle with care and avoid spillage on the floor (slippage).  
Keep away from sources of ignition:  
Bond and ground handling equipment and transfer containers to prevent parking.  
Do not cut, weld, drill, grind, braze, or solder container.

#### **D.O.T. SHIPPING INFORMATION**

NA 1993, Class: -, Proper Shipping Name: Combustible liquid, n.o.s.  
Technical Shipping Name: Contains Petroleum Naphtha, 1,2,4-Trimethylbenzene  
Packing Group: III

BATCH NUMBER:

**NA 1993**