

NEOPRENE SEALANT is a unique, professional-grade, elastomeric flashing and repair product that cures to a long lasting rubber membrane. This product remains flexible through extreme temperature ranges. The non-sag properties and exceptional adhesion guarantees that **NEOPRENE SEALANT** is the ideal cement for the construction and repair of all flashings, parapet walls, coping and chimneys. This product is ideally suited for sealing cracks, holes and tears in built-up roofs (asphalt and tar) and modified bitumen single plys. **NEOPRENE SEALANT** is an excellent cement for sealing gaps in sheet metal roofs. It may also be used for adhering shingle tabs or any other roofing material.

DIRECTIONS

SURFACE PREPARATION: All surfaces to be treated must be dry and free from oil, grease and other foreign materials. The surface must be firm and free from loose material or excessive dust. On very porous surfaces such as some concrete, stucco and insulation, priming is recommended before application. All loose nails must be drive in and capped with **NEOPRENE SEALANT**. On composition roofs, open any breaks or blisters to be patched and permit to dry out before filling with this product.

APPLICATION AND COVERAGE: This product is designed to be applied with a trowel. Spray evenly and smooth out as much as possible. Apply to a minimum wet thickness of ¼". Permit to dry 24 hours before coating with an elastomeric coating. Tools are best cleaned with Xylol.

Coverage will vary with thickness of application, but will average approximately 6 square feet per gallon.

CAS NUMBERS: Contains Xylol (1330-20-7), mica (12001-26-2), ethylbenzene (100-41-4), and carbon black (1333-86-4).

Gmp
Chemical Solutions

RD910

GENERAL MAINTENANCE PRODUCTS

NEOPRENE SEALANT

Flashing Cement

- ✓ Asbestos free
- ✓ High performance, rubberized, elastomeric cement
- ✓ Remains flexible and watertight for up to 20 years
- ✓ Up to 50 times stronger than plastic roof cement

CAUTION: See side panel for precautionary information.

KEEP OUT OF REACH OF CHILDREN.
NET CONTENTS 5 GAL(S)

CAUTION

Keep away from heat and open flame. Use only with adequate ventilation. Avoid prolonged or repeated contact with skin and breathing of vapor. Do not take internally. Seal container when not in use. Storage of material should be in a cool, shaded area during hot weather and as close to room temperature as possible during cold weather. VOC = 420 g/l maximum. This product contains less than 3.8 pounds of VOS per gallon of coating, excluding water.

FIRST AID

IF IN EYES: Flush with large amounts of water. If irritation persists, seek medical attention.

IF ON SKIN: Wash with soap and water. If irritation persists, seek medical attention.

IF INHALED: Remove person from affected area to fresh air. If irritation persists, seek medical attention.

IF SWALLOWED: Do not induce vomiting. Contact a physician immediately.

KEEP OUT OF REACH OF CHILDREN.

Reorder RD910
800-548-2080

SOLD EXCLUSIVELY BY:


General Products & Supply Inc.

Murrysville Business Park
Export, PA 15632

HMIS RATING
3 - FLAMMABILITY
2 - HEALTH
0 - REACTIVITY
C- PERSONAL PROPERTY

Gmp
Chemical Solutions

101 Technology Lane
(800) 548-2080