

LIQUID FIBERED ASPHALT ROOF COATING is a heavy bodied, asphalt coating used to resaturate, preserve and protect composition and build-up on smooth or granulated roll roofing. This coating can also be used on metal roofs and exterior foundation walls. Do not se on shingle roofs.

DIRECTIONS

Remove all dust, dirt and debris. Roof should be completely clean and dry before applying coating. Older, dried out roofing felts should be primed with **NON-FIBERED ALUMINUM ROOF COATING**. Repair all cracks, breaks or open seams and allow to dry before coating. Remove all rust or loose paint from metal surfaces. Galvanized roofing should be allowed to weather one year before coating.

For coating the entire roof, apply a heavy coat with a squeegee, roof brush or mastic type spray gun. Coverage should be approximately 1.5-4.0 gallons per 100 square feet depending on type and porosity of surface being coated. When coating exterior foundation walls, allow 48 hours before back filling.

CAS Numbers: Contains Petroleum Asphalt (8052-42-4), Mineral Spirits (8052-41-3), and Chrysotile Asbestos—Encapsulated (12001-29-5).



GENERAL MAINTENANCE PRODUCTS



CAUTION

Keep in a heated room until ready to use since coating will thicken in cold weather. Do not use on shingle roofs. Do not apply over damp or wet surfaces. Contains petroleum distillates. Keep away from sparks, heat and open flame. Use only with adequate ventilation. Avoid prolonged or repeated contact with skin and breathing of vapor. Seal container when not in use. Meets ASTM D 4479, Type III; RCMA Specification No. 2; Federal Specifications SS-A-694D. VOC = 300g/l max. This product contains less then 2.5 pounds of VOS per gallon of coating, including water.

FIRST AID

IF IN EYES: Flush with large amounts of water. IF irritation persists, seek medical attention.

IF ON SKIN: Wash with soap and water. If irritation persists, seek medical attention.

IF INHALED: Remove person from affected area. If breathing is difficult, administer oxygen. If breathing has stopped, give artificial respiration.

IF SWALLOWED: Do not induce vomiting. Seek medical attention immediately.

Reorder RD915
800-548-2080

HMIS RATING
2 - FLAMMABILITY
2 - HEALTH
0 - REACTIVITY
-- PERSONAL PROPERTY

SOLD EXCLUSIVELY BY:


General Products & Supply Inc.

Murrysville Business Park
Export, PA 15632

GMP
Chemical Solutions

101 Technology Lane
(