

ALL PURPOSE FIBERED ROOF CEMENT is used for a variety of roof repairs. This trowel-grade cellulose fibered cement is ideal for temporary repairs while the roof surfaces are cold and wet, and for more permanent repairs before coating with other types of fibered roof coating.

ALL PURPOSE FIBERED ROOF CEMENT can be used for patching cracks and breaks in roofing surfaces, firewalls, chimneys, gutters and flashings. It can also be used for installing new flashing. **ALL PURPOSE FIBERED ROOF CEMENT** will stop leaks when applied around vent pipes, in valleys, around spouts, skylights, gutters and chimneys. It can be used to line leaky gutters and troughs, and to seal cracks in chimneys, walls and foundations.

This durable mastic is recommended for repairs before coating surfaces with roof coatings. Do not use on wood, slate shingles or tar roofs. Do not use over PVC, plastic membranes, coal tar or silicone. Do not use where it will come in contact with potable water.

This product has excellent adhesion to damp as well as dry surfaces. It is heavily plasticized to give outstanding durability, and will remain soft and pliable longer than ordinary plastic cements.

Normal patching and flashing work is done in one operation, rather than the usual steps of plastic application, membrane, and another layer of plastic cement.

It is especially formulated to apply easily in cold temperatures and at the same time, it will not run or sag on vertical flashings under hot, sunny conditions. No other plastic cement combines all of these features in one product, nor does any other have such unusual durability.

DIRECTIONS

PREPARATION: Surface should be clean & dry. Remove dust, dirt, and debris using stiff brush or broom. Remove crusted rust or scaled, previous coating by scraping or wire brushing.

COMPOSITE ROOFS: Replace all drawn up nails with larger nails before patching. If roof is dried out, apply asphalt primer before patching.

CONCRETE ROOFS: Prime with asphalt primer before patching.

METAL ROOFS: Re-nail loose laps with longer nails to stop vibration.

APPLICATION: Apply with trowel or putty knife. Occasionally dipping trowel in mineral spirits will reduce sticking to tools.

Gmp
Chemical Solutions

RD924

GENERAL MAINTENANCE PRODUCTS

ALL PURPOSE FIBERED ROOF FLASHING CEMENT

- Forms Its Own Membrane
- Stronger Than Plastic Roof Cements
- Applies Easily in Cold Weather
- Easy Troweling, Resists Cracking

KEEP OUT OF REACH OF CHILDREN.

NET CONTENTS 5 GAL(S)

DIRECTIONS (CONT.)

To patch holes or cracks, fill with plastic cement and smooth down edges. Apply this cement at least 1/4" thick. For easiest workability in very cold weather, keep this material in a heated room before using. One gallon covers approximately 6 to 7 square feet, depending on repair being done.

Clean Up: For tools use mineral spirits. **For skin use: GMP SOY HAND SCRUB.**

CAS Numbers: Contains petroleum asphalt (8052-42-4), mineral spirits (8052-41-3), clay (12174-11-7) and cellulose fiber (9004-34-6).

CAUTION

Contains petroleum distillates. Keep away from heat, sparks and open flame. Use only with adequate ventilation. Avoid prolonged or repeated contact with skin and breathing of vapor. Do not take internally. Seal container when not in use.

CONTAINER DISPOSAL

Empty containers contain residue (vapor & Liquid) all labeled precautions must be observed. Do not reuse container. Dispose of empty container in accordance with all applicable local, state and federal regulations.

KEEP OUT OF REACH OF CHILDREN



Reorder RD924
800-548-2080

HMIS RATING	
1 - HEALTH	
2 - FLAMMABILITY	
0 - REACTIVITY	
B - PROTECTIVE EQUIPMENT	

SOLD EXCLUSIVELY BY:


General Products & Supply Inc.

Murrysville Business Park
Export, PA 15632

Gmp
Chemical Solutions

101 Technology Lane
(800) 548-2080