

**P. MODIFIED DRIVEWAY COATING** is a mineral reinforced, asphalt emulsion pavement sealer designed to protect and beautify asphalt pavement surfaces. It is fortified with sand for added slip resistance. Color is black when dry.

**P. MODIFIED DRIVEWAY COATING** is used for any asphalt pavement surface including parking lots, driveways, airports, roadways, secondary roads, highway shoulders, walkways, and more.

New asphalt surfaces should be allowed to cure a minimum of four weeks under ideal weather conditions before application. Surface must be clean and free from all loose material, dirt, and dust. For ease of application in hot weather, the surface may be fogged with water prior to sealing. Pavement surface repairs should be made with a suitable hot or cold asphalt mix. Cracks should be filled with hot or cold applied crack fillers. Treat all grease, oil, and gasoline spots or stains before applying sealer.

**DIRECTIONS:**

**Stir well before using. Do not dilute. Use as is.**

Two coats of **P. MODIFIED DRIVEWAY COATING** are recommended. Apply by squeegee, brush, or spray. Apply second coat in cross direction to the first. Allow first coat of sealer to dry a minimum of 2 to 4 hours under ideal weather conditions (above 70°F, low humidity) before applying second coat. Allow longer drying time between coats when temperature is below 70°F. Allow a minimum of 8 hours and preferably 24 hours before parking cars or allowing traffic over the surface.

**Gmp**

Chemical Solutions

RD941

**GENERAL MAINTENANCE PRODUCTS**

**P. MODIFIED  
DRIVEWAY COATING**

**Polymer Emulsion  
Driveway Sealer**

- Easy to Stir & Spread
- Resists Oil & Gasoline
- More Compatible with Asphalt than Coal Tar
- Blacker than Conventional Sealers
- Environmentally Friendly
- Low Odor, Contains NO Skin Irritants

**KEEP OUT OF REACH OF CHILDREN.**

**NET CONTENTS: 5 GAL(S)**

Covers 60 to 90 square feet per gallon for one coat depending on age, pavement porosity, and method of application.

Wash tools in water.

**CAUTION:** Do not take internally. If swallowed, call a physician immediately. In case of contact with eyes, flush immediately with water for 15 minutes and call a physician. When not in use, keep containers tightly closed and upright to prevent leakage.

**KEEP OUT OF REACH OF CHILDREN.**



Reorder RD941  
800-548-2080

**HMIS RATING**

-- FLAMMABILITY

-- HEALTH

-- REACTIVITY

-- PERSONAL PROPERTY

SOLD EXCLUSIVELY BY:

  
General Products & Supply Inc.

**Gmp**  
Chemical Solutions

Murrysville Business Park  
Export, PA 15632

101 Technology Lane  
(800) 548-2080