

POURABLE DRIVEWAY CRACK SEALER is excellent for filling cracks up to ½" wide in any blacktop or concrete surface. This product dries to a rubber hard consistency and is easy to use.

Proper use of **POURABLE DRIVEWAY CRACK SEALER** helps prevent freeze-thaw action on driveways that could result in larger cracks and breaks if small cracks are not filled. The cured sealer is a solid base for traffic, and on blacktop provides an excellent filler prior to application of driveway coating. This product applies easily by pouring, permitting simple filling of small cracks up to ½" wide.

POURABLE DRIVEWAY CRACK SEALER has a long storage life and can be applied to any blacktop or concrete surface, with proper preparation, as long as the outdoor temperature is 50°F (10°C) or higher.

DIRECTIONS

Surface must be clean, free of loose materials, dirt and dust. Crack may be cleaned with water. Shake container before using. Do not dilute. Pour into crack, which is preferably damp (not wet), filling to slightly above surface. For best results, do not apply when temperatures are below 50°F (10°C). Do not use in cracks wider than ½". (Cracks over ½" deep require partial filling with sand prior to pouring crack sealer.)

Allow to harden before permitting traffic. Do not use when rain is imminent. The filled crack must be protected from water contact for 6 daylight hours under normal drying conditions. Keep from freezing in container. Wash tools with water. Dried material may be cleaned with paint thinner or kerosene.

CAS NUMBERS: Contains no hazardous materials.

Gmp
Chemical Solutions

RD945

GENERAL MAINTENANCE PRODUCTS

POURABLE DRIVEWAY CRACK SEALER

**Fills Cracks in Blacktop
and Concrete Driveways**

- ✓ Fast Drying
- ✓ Easy Application
- ✓ Fills Cracks Up to ½" Wide
- ✓ Dries to a Rubbery Hardness

CAUTION: Combustible. See additional precautionary information on side panel.

KEEP OUT OF REACH OF CHILDREN.

NET CONTENTS 1 GAL(S)

CAUTION

Combustible. Keep away from heat, sparks and open flame. Use only with adequate ventilation. Avoid prolonged or repeated contact with skin and breathing of vapor. Do not take internally. Seal container when not in use.

FIRST AID

IF IN EYES: Flush with large amount of water. Contact a physician.

IF ON SKIN: Wash with soap and water. If irritated, contact a physician.

IF SWALLOWED: Contact a physician immediately.

KEEP OUT OF REACH OF CHILDREN.



Reorder RD945
800-548-2080

HMIS RATING
0 - FLAMMABILITY
0 - HEALTH
0 - REACTIVITY
B - PERSONAL PROPERTY

SOLD EXCLUSIVELY BY:


General Products & Supply Inc.

Gmp
Chemical Solutions

Murrysville Business Park
Export, PA 15632

101 Technology Lane
(800) 548-2080